

**EQUIPMENT SPECIFICATION
COUNTY PKG 10 (9-02)
TRANSMISSION MOUNTED P.T.O.
STEEL HYDRAULIC DUMP BED
14 FEET LENGTH**

GENERAL: THIS SPECIFICATION SHALL PROVIDE FOR STEEL HYDRAULIC DUMP BEDS, NEW, THE LATEST CURRENT PRODUCTION MODEL. COMPLETE WITH MANUFACTURER'S CERTIFICATION OF WARRANTY AND BE BID LESS ALL APPLICABLE STATE AND FEDERAL TAXES. (WARRANTY SHALL BE THE STANDARD FOR THE INDUSTRY AS OFFERED TO THE GENERAL PUBLIC.) THIS BODY SHALL BE EQUIPPED TO MEET ALL FEDERAL AND STATE OF OKLAHOMA SAFETY STANDARD AND REQUIREMENTS. NO DEALER ADVERTISEMENT SHALL BE AFFIXED TO BED.

FILL IN ALL SPACES SHOWING SPECIFIC INFORMATION, FAILURE TO COMPLY COULD RESULT IN BID REJECTION.

VENDOR'S PROPOSED:

MAKE: Godwin
MODEL: 400T
PRICE EACH: \$12968.00

MINIMUM REQUIREMENTS

BODY SIZE: CAPACITY: 10 YDS. WATER LEVEL, 12 YD. W/SIDE BOARD EXTENSIONS.
PROPOSAL BID: Comply

LENGTH 14 FEET
PROPOSAL BID: Comply

WIDTH: 84 OR 87 INCHES
PROPOSAL BID: Comply

HEAD HEIGHT: 44 INCHES
PROPOSAL BID: Comply

TAIL GATE HEIGHT: 44 INCHES
PROPOSAL BID: Comply

SIDE HEIGHT: 36" WITH 3 1/2" BOXED TOP RAIL DIRT SHEDDING
PROPOSAL BID: Comply

STEEL THICKNESS: 10 GAUGE GRADE 50 HI-TENSILE
PROPOSAL BID: Comply

FLOOR: 2" RADIUS FLOOR TO SIDE WALL FOR EASY CLEAN OUT. 3/16" ONE PEICE
GRADE 50 HI-TENSILE.
PROPOSAL BID: Comply

CROSS MEMBERS: 8 EACH, 4" C' SECTION 5.4# GRADE 50 HI-TENSILE.
PROPOSAL BID: Comply

LONGITUDINAL: 7" STRUCTURAL CHANNEL 12.25#.
PROPOSAL BID: Comply

CORNER POSTS REAR: 2 EACH, 10" FULL DEPTH W/EXTRA BRACES
PROPOSAL BID: Comply

SPREADER CHAINS: 2 EACH
PROPOSAL BID: Comply

RUB RAILS: FULL LENGTH SLOPING PROPOSAL BID: Comply

BASE WEIGHT: SHOW BASE WEIGHT OF BODY (WITHOUT HOIST & ACCESSORIES)
PROPOSAL BID: 3886#

LIGHTS: TWO LED STOP, TURN, OVAL TYPE INSTALLED IN REAR VERTICAL BOLSTERS.
PROPOSAL BID: Comply

CLEARANCE LIGHTS: 4 LED, 1 EACH CORNER ICC APPROVED TO BE INSTALLED UNDER CORNER OF BED, FRONT AND REAR.
PROPOSAL BID: Comply

6 METAL BASE REFLECTORS: 2 EACH SIDE, 2 REAR MOUNTED ON END GATE, LCC APPROVED. NOTE: THESE REFLECTORS MUST BE HOUSED TYPE WITH SCREW OR BOLT TYPE MOUNTING STICK-ON TYPE IS NOT ACCEPTABLE.
PROPOSAL BID: Comply

TAILGATE: DOUBLE ACTING W/FULLY WELDED BOX TYPE HORIZONTAL BRACING & OFFSET HARDWARE.
PROPOSAL BID: Comply

BANJO EYES: 2, 1 EACH SIDE & EXTEND BEYOND REAR POST
PROPOSAL BID: Comply

SIDE BOARD BRACES: 5" BOX TYPE CONTINUOUS WELD
PROPOSAL BID: Comply

SIDE BOARD GUSSETS: 4 EACH, 6" HIGH, 3" WIDE
PROPOSAL BID: Comply

BANG BOARDS 2"X10" TREATED PINE
PROPOSAL BID: Comply

MUD FLAPS: 2, 1 EACH SIDE 24" X 30" ON-SAIL TYPE & QUALITY TO BE WITHOUT ANY ADVERTISEMENT.
PROPOSAL BID: Comply

TAILGATE HARDWARE: UPPER OFFSET TAILGATE HINGES. LOWER TAILGATE PINS SHALL BE 1-1/4" DIAMETER MINIMUM. LOWER BODY HARDWARE SHALL BE OF THE OVERHEAD TYPE HOOKS & RETAIN THE 1-1/4" PINS TO SUPPORTS OF EACH SIDE OF THE HOOK.
PROPOSAL BID: Comply

MOUNTING HEIGHT: NOT TO EXCEED 12 - 3/4" FROM TOP OF TRUCK FRAME TO FLOOR OF BODY.
PROPOSAL BID: Comply

CAB COVER: CAB COVER APPROXIMATELY 1/2 OVER TRUCK CAB MOUNTED ON FRONT OF DUMP BID.
PROPOSAL BID: Comply

SAFETY STRUT: ALL DUMP BEDS MUST BE EQUIPPED W/ 2 SAFETY STRUTS TO HOLD BED IN 'UP' POSITION WHILE REPAIRS ARE BEING MADE.
PROPOSAL BID: Comply

BODY UP LIGHT: TO BE INSTALLED TO WARN OPERATOR IF DUMP BODY IS NOT FULLY DOWN.
PROPOSAL BID: Comply

BACK UP ALARM: ELECTRICAL TYPE TO BE INSTALLED.

PROPOSAL BID: Comply

HYDRAULIC HOIST: G63120T CLASS 90

SHOW HOIST: Brochure Attached

SHOW MAKE: Godwin

SHOW MODEL: G63120T C102D

CYLINDER: SHOW INSIDE DIAMETER & PISTON DIAMETER AND STROKE. 6"
1ST ACTIVE SLEEVE, 5" 2ND, 4" 3RD, 7" AND BASE
TUBE 120" STROKE, SINGLE ACTING SELF ADJUSTING V TYPE PACKING INTERIOR
GUIDE BUSHING - BRONZE OR POLISHED STEEL SLEEVE.

PROPOSAL BID: Comply

HOIST CAPACITY: 20 TONS

PROPOSAL BID: Comply

DUMP ANGLE: 50 DEGREES MAXIMUM

PROPOSAL BID: Comply

BLEEDER VALVE: AT TOP OF BASE SLEEVE.

PROPOSAL BID: Comply

OIL RESERVOIR: CAPACITY ADEQUATE TO EXTEND CYLINDER.

PROPOSAL BID: Comply

REAR PIVOT HINGE: DOUBLE SHEAR TYPE - 2 HINGE PINS 2" X 7" (NO SUB FRAMES). A
1/2" PLATE SHALL BE ADDED UNDER REAR PIVOT TO FILL IN SPACE BETWEEN FRAME
FOR REINFORCEMENT.

PROPOSAL BID: Comply

STEP: REQUIRED TO BE LOCATED AT THE REAR OF CURBSIDE BODY BETWEEN THE
BOLSTER AND THE FIRST VERTICAL RIB. WITH 2-RUNG (BUYERS MODEL RS2 OR
EQUAL) SLIDE OUT LADDER TO BE BELOW BODY LADDER

PROPOSAL BID: Comply

HYDRAULIC PUMP: DIRECT MOUNT THREE LINE SYSTEM TO PTO. INSTALLER MUST
INSTALL BRACKET TO SUPPORT PUMP SO PTO DOES NOT BREAK. (NO DRIVE LINE)
25 GPM AT 1000 RPM AND 1800 PSI GEAR TYPE.

PROPOSAL BID: Comply

RELIEF VALVE: BUILD INTO TANK OR PUMP, SHOW

PROPOSAL BID: Comply

SHAFT BEARINGS: ROLLER BEARING STANDARD.

PROPOSAL BID: Comply

CONTROL VALVE: 3 POSITION (RAISE, HOLD AND LOWER) SPRING LOADED TO
NEUTRAL.

PROPOSAL BID: Comply

CONTROLS: CONSOLE ON FLOOR, WITH LOCKING DEVICE IN NEUTRAL
FOR DUMP, IN & OUT FOR POWER TAKE OFF, WITH LIGHTED PANEL. CONTROLLED
WITH SEALED STAINLESS STEEL CABLE FROM CENTRAL BOX OR AIR CONTROL TO
CONNECTORS FOR PUMP AND POWER TAKE OFF

PROPOSAL BID: Comply

FOR MANUAL TRANSMISSION

SHOW MAKE: Muncie
SHOW MODEL: TG8S-A6807-A1KX

MOUNTING INSTRUCTIONS: THE DUMP BED SHALL BE MOUNTED THREE (3) INCHES BACK TO TRUCK CAB. THE FRONT MOUNTING BRACKETS ON EACH SIDE OF THE FRAME SHALL BE DRILLED AND BOLTED, NOT WELDED TO THE TRUCK FRAME.

THE FOLLOWING REQUIREMENTS WILL BE NECESSARY IF THERE IS NO SAFEGUARD TO PREVENT THE BED FROM BEING RAISED TOO HIGH OR BEYOND THE RETURN POINT OF THE HYDRAULIC HOIST CYLINDERS.

SAFETY BED STOP BLOCKS OF SUFFICIENT THICKNESS TO PROVIDE THIS PROTECTION MUST BE MOUNTED BEHIND THE BED HINGES BETWEEN THE BED AND THE TRUCK FRAME.

NOTE: THE DELIVERY AND INSTALLATION (IF SPECIFIED) WILL BE THE SOLE RESPONSIBILITY OF THE BIDDING VENDOR, WHO MUST ESTABLISH A PRIORITY SCHEDULE BASED ON THE DATE OF THE PURCHASE ORDERS. INSTALLATIONS WILL BE MADE AT THE RATE OF 1 UNITS PER DAY; STARTING 15 DAYS AFTER THE NEW TRUCK ARE DELIVERED TO THE INSTALLATION POINT.

COMPLETE THE FOLLOWING:

GIVE NAME, ADDRESS AND PHONE NUMBER OF PERSON RESPONSIBLE FOR DELIVERIES AND INSTALLATION:

NAME: Kurt Olson or Kurt Schroeder / Southwest Trailers & Equipment L.L.C.
ADDRESS: 10400 West Reno Oklahoma City, OK 73127
PHONE NUMBER: (800) 375-6307 (405) 943-9851

NOTE: BED VENDOR MUST NOT REMOVE IDENTIFICATION PLATES OR NUMBERS ON THE TRUCK. THIS ESPECIALLY APPLIES TO THE TRUCK TRANSMISSION WHEN POWER TAKE-OFF IS INSTALLED. IF, DURING INSTALLATION, IT BECOMES NECESSARY TO REMOVE THESE PLATES OR COVER THESE NUMBERS, THEY MUST BE REPLACED IN A VISIBLE LOCATION.

ELECTRICAL WIRING: WIRING TO BE IN LOOM AND PROPERLY SECURED TO FRAME TO PREVENT SAGGING. ALL WIRE CONNECTIONS SHALL BE MADE WITH HEAT SHRINK CONNECTORS OR WEATHER PACKS. ALL LIGHT WIRING FOR BODY WILL BE THROUGH A JUNCTION BOX MOUNTED AT REAR OF BODY. THIS INSULATION MATERIAL TO BE OF SUFFICIENT QUALITY TO INSURE A LIFE OF FIVE (5) YEARS.

PROPOSAL BID: Comply

POWER TAKE OFF: MUST BE THE LATEST CURRENT MODEL INSTALLED AND/OR ADAPTED TO FIT THE TRANSMISSION. MOUNTING BOLTS OR SCREWS MUST PROVIDE ADEQUATE SELF-LOCKING AND SEALING TO INSURE AGAINST OIL LEAKS, AND MUST KEEP HOUSING FIRMLY ATTACHED TO TRANSMISSION.

PAINT: HOISTS, BODY, AND ALL EXPOSED METAL SHALL BE ZINC POWDER COAT PRIMED AND POWDER TOP COAT WITH STANDARD PRODUCTION COLOR AS ORDERED AT NO EXTRA COST. TOP COAT AND ZINC TO BE LAB CERTIFIED TO WITHSTAND NO LESS THAN 4000HRS ACCELERATED SALT SPRAY TEST BASED ON 5% SALT SOLUTION. THEN BE PAINTED A STANDARD PRODUCTION COLOR AS ORDERED AT NO EXTRA COST.

PROPOSAL BID: Comply

PARTS: BIDDER SHALL FURNISH UPON REQUEST A LIST OF ESTABLISHED MANUFACTURER'S AUTHORIZED LOCATIONS WHERE AND ADEQUATE STOCK OF CURRENT PARTS AND SERVICE ARE AVAILABLE.

MANUAL AND PARTS BOOK: SUCCESSFUL BIDDER SHALL FURNISH ONE (1) OPERATOR'S INSTRUCTION MANUAL FOR EACH UNIT, IN ADDITION, ONE (1) PARTS BOOK AND ONE (1) ILLUSTRATED MANUAL SHALL BE FURNISHED TO EACH DIVISION PURCHASING ONE OR MORE BODIES.

SERVICE POLICY: MANUFACTURER'S STANDARD SERVICE POLICY SHALL BE FURNISHED COMPLETE AND UNALTERED, WITH EACH UNIT DELIVERED. MANUFACTURER SHALL BE RESPONSIBLE THAT SATISFACTORY SERVICE (BY OTHER THAN THE DEALER SELLING UNIT) IS RENDERED UPON PRESENTATION OF PROPER SERVICE POLICY PAPERS.

NOTE: INSTALLATION, SERVICE AND WARRANTY MUST BE PROVIDED WITHIN THE STATE OF OKLAHOMA.

COMPLIANCE: BIDDER SHALL FILL IN ALL SPACES SHOWING SPECIFIC INFORMATION. BIDDER SHALL FURNISH A STATEMENT IN WRITING IF EQUIPMENT PROPOSAL STRICTLY MEETS OR EXCEEDS THESE MINIMUM SPECIFICATIONS, IF IT DOES NOT, HE SHALL LIST EACH VARIATION THEREFROM, FAILURE TO COMPLY COULD RESULT IN BID REJECTION.

THE STATE OF OKLAHOMA RESERVES THE RIGHT TO WAIVE MINOR TECHNICALITIES UNDER THESE SPECIFICATIONS.

VENDOR'S STATEMENT: (EQUIPMENT PROPOSED COMPLIES) YES X NO

DEALER: Southwest Trailers & Equipment L.L.C.

SIGNATURE: _____

ADDRESS: 10400 West Reno Oklahoma City, OK 73127

PHONE: (800) 375-6307 (405) 943-9851 DATE: 6/18/2012