



Fire Apparatus Quotation for:  
SUNBELT FIRE, INC



Quotation Number: 77427 Rev: 10

Unit Description: PMPR-COMM

Quote Description: Pumper, Commercial Chassis

Salesperson: DRHODES

2-door Commercial Pumper

Salescode	Extended Description	Qty
TESTING COMPLIANCE STANDARD		
1001-0065	The E-ONE supplied components of the vehicle shall meet the requirements of NFPA 1901, 2016 edition.	1
CHASSIS PREP		
1020-0010	Comm Chassis Prep E-1 Supp-FL.	1
AXLE OPTIONS		
1025-0042	Front axle for commercial chassis 12,000 lb. rating.	1
1025-0046	Rear axle for commercial chassis 23,000lb rating	1
TIRE OPTIONS		
1060-0117	RWC AirGuard LED tire pressure monitoring valve stem caps (6) for single rear axle applications.	1
AIR SYSTEM OPTIONS		
1110-0010-277	Air inlet. To charge brake system. Commercial chassis only. Location: driver's door step area.	1
1110-0076	Dual Stuttertone hood mounted air horns with driver and officer foot switches to be supplied and installed by Freightliner.	1
ENGINES & TRANSMISSIONS		
1200-0126	Chassis speed to be electronic limited and not to exceed a maximum of 68 MPH. Note: Speed rating may be lower based on OEM tire ratings/top speed limitations provided on chassis.	1
1200-0286	Freightliner Cummins ISB 360 HP, 800 lb-ft Torque, 2013 EPA engine.	1
CHASSIS OPTIONS		
1680-0011	Tow eyes rear below body, painted.	1

Salescode	Extended Description	Qty	
<b>CHASSIS OPTIONS</b>			
1680-0078	Tow hooks front OEM. Not available with extended E-ONE installed front bumper. Tow hooks are OEM supplied with chassis.	1	
1680-0104	OEM chassis step package for Freightliner M2 series. Includes mounting plate for the battery charger receptacle and air inlet.	1	
1680-0235-R01	The batteries to be located under left hand side of cab.	1	
<b>CAB MODEL</b>			
1500-0008	Two door Freightliner M2 106 4x2	1	
<b>CAB BADGE PACKAGE</b>			
1610-0000	Cab and body to have applicable E-ONE logos.	1	
<b>CAB DOOR OPTIONS</b>			
1550-0059-000-G6	Reflective Red/Lemon Yellow printed striping positioned in the "A" formation located on the cab door panels.	1	
<b>MISC EXTERIOR CAB OPTIONS</b>			
1675-0007	Diesel fuel only label.	1	
<b>SEATS</b>			
1685-0030	Seating capacity tag of three occupants.	1	
<b>CAB ELECTRICAL OPTIONS</b>			
1750-0059-277-04	Receptacle inlet 20 amp with a Yellow cover. Location: driver's door step area.	1	
1750-0343	Battery charger E-ONE LPC 20, 120 volt inlet, 20 amp output.	1	
<b>BODY COMPT LEFT SIDE</b>			
3100-0094	Driver side body with full height 30" wide forward and 36" wide rearward compartmentation. Includes (1) 56" wide compartment over the wheel well.	1	
<b>BODY COMPT RIGHT SIDE</b>			
3120-0003	Officer half side body with 30" wide forward and 36" wide rearward compartmentation. Includes adjustable ladder tracks.	1	
<b>BODY COMPT REAR</b>			
3110-0005	Full Height Rear Compartment. Includes smooth plate panels.	1	
3110-0034	Upper rear compartment depth to be shallow.	1	
3340-0080	Bolt-on diamond plate 18" tailboard (full width of body). Includes (2) squared off beaverails (no stanchions) with removable outer panels and handrails- (2) vertical on trailing edge of body and horizontal mounted handrail(s) below	1	



Salescode	Extended Description		Qty	
BODY COMPT REAR				
	hosebed.			
DOORS				
3300-0007-003	Door single vertical hinged painted. Location(s): L1	1		
3300-0007-015	Door single vertical hinged painted. Location(s): R1	1		
3300-0011-004	Door single horizontal hinged lift-up box pan configuration painted. Location(s): L2	1		
3300-0164-016	Door double vertical hinged w/rotary latches - painted. Location(s): R2	1		
3300-0167-005	Door double 3-point vertical hinged w/rotary latches - painted. Location(s): L3	1		
3300-0169-027	Door double 3-point vertical hinged w/rotary latches - smooth plate sanded. Location(s): B1	1		
COVERS				
3305-0007-000-13	Vinyl Black hose bed cover with attached rear flap(s).	1		
3305-0008-000-13	Vinyl Black crosslay cover with attached side flaps.	1		
PUMP MODULE				
3130-0167	Pump module to be 76" wide (side to side). Includes upper, lower, crosswalk, speedlay and transverse module(s) if applicable.	1		
3130-0523	Side mount pump module. Extruded aluminum with runningboards.	1		
3130-0532	Pump panel opening is 39" wide. Pumper / tanker only.	1		
3130-0539	Pump module height is 75". Pumper / tanker only.	1		
PUMP PANELS				
3134-0016	Stainless steel driver and officer side pump panels.	1		
3134-0143	Officer side pump panel to be vertical hinged on forward extrusion. Panel to be (3) pieces with upper (2) panels secured in the closed position with push button latches. Upper panel to be held open with gas shock.	1		
MISC PUMP PANEL OPTIONS				
4460-0003	Pump panel tags color coded per NFPA compliance.	1		
PUMP MODULE OPTIONS				
3136-0058	E-ONE logo mounted one each side on pump module/preconnect panels. Logos to be sized as applicable to available space on panels.	1		
3136-0138	Pump module storage pan.	1		
3136-0139	Crosslay double 7.5" wide each to hold up to 200' of 2.0" DJ hose (each).	1		



Salescode	Extended Description	Qty	
<b>WATER TANK</b>			
4010-0099	Fill tower(s) to be located offset to officer side of water tank.	1	
4010-0174	530 Gallon "T" Water Tank. UPF Poly III color fill towers. Note: Any foam cell(s) will reduce the overall water capacity.	1	
<b>TANK PLUMBING</b>			
4450-0010	2" tank fill Akron manual valve.	1	
4450-0119	3" tank to pump Akron manual valve w/4" tank connection.	1	
<b>LADDER STORAGE / RACKS</b>			
3365-0031	Hard Suction Storage Rack. Officer side in adjustable track above ladders (if applicable). Includes spring hold downs and scuff plates.	2	
3365-0049	Brand of ladders capable of being carried on unit to be Alco-Lite.	1	
3365-0087-C57	The length of ladders capable of being stored shall be the following: 24' 2-section and 14' roof ladder.	1	
<b>HANDRAILS / STEPS</b>			
3330-0277	Innovative Controls dual lighted LED folding steps rear NFPA. Includes folding steps on driver side (staggered stepped as applicable with tailboard depth) for NFPA hosebed access and handrail mounted on driver side upper hosebed side (as applicable).	1	
<b>MISC BODY OPTIONS</b>			
3000-0000	Body mainframe and hosebed side assemblies for a 80" high body.	1	
3090-0002	OAH. Unit has no overall height restrictions.	1	
3090-0004	OAL. Unit has no overall length restrictions.	1	
3090-0007	Hosebed hoseload allowance on the apparatus shall be 1200 lbs.	1	
3340-0004	Hosebed above the booster tank. Includes forward hosebed and tower(s) cover plate work (as applicable). Hosebed adjustable divider extrusion rearward of the furthest tower is to run full width of the hosebed (as is practical with other hosebed mounted equipment).	1	
3340-0015	Diamond plate single axle wheel well. Includes bolt-on composite wheel well liners and aluminum trim fenderettes.	1	
3340-0035	Divider Long. To run full length of hose bed (front to rear).	1	
3340-0093	Mud flaps, rear, black with E-ONE logo.	1	
3340-0110	The rear of each hose bed divider to have a hand hold cut-out(s).	1	
3340-0145	Rub rail for the body and pump area module(s).	1	
3340-0681	Body mainframe layout line to be 24". Includes body and all applicable modules.	1	



Salescode	Extended Description	Qty	
<b>MISC BODY OPTIONS</b>			
3340-1137-12B	Equipment allowance on the apparatus shall be 2000 lbs. This allowance is in addition to the weight of the hoses and ground ladders listed in the shop order as applicable.	1	
<b>PUMPS</b>			
4005-0030	Rating 1250 GPM	1	
4005-0195	Hale QFLO 750-1250 GPM pump, single stage. Requires primer option.	1	
<b>PUMP CERTIFICATION</b>			
4475-0000	Pump certification 750-2250 GPM	1	
<b>PUMP OPTIONS</b>			
4015-0029	Hale pressure relief valve.	1	
4015-0037	Engine throttle, vernier.	1	
4015-0053-198	Steamers to be Flush + 1". Location: driver's side.	1	
4015-0053-199	Steamers to be Flush + 1". Location: officer's side.	1	
4015-0098	Manual operated master pump drain. The master drain shall be clearly marked and placed in accessible location on pump panel.	1	
4015-0238	Hale electric primer (oil-less).	1	
<b>INTAKES</b>			
4440-0005	2.5" Left Intake Akron Manual Valve.	1	
<b>INTAKE OPTIONS</b>			
4445-0048	Intake pressure relief valve, Task Force Tips.	1	
<b>DISCHARGES AND PRECONNECTS</b>			
4415-0012-654	1.5" Crosslay with Akron manual valve. Location: crosslay 1 & 2.	2	
4415-0014-581	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 1.	1	
4415-0014-582	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 2.	1	
4415-0016-583	2.5" Right Pump Panel Discharge Akron Manual Valve. Location: right side discharge 1.	1	
4415-0022-350	2.5" Left Rear Discharge Akron Manual Valve. Location: left rear discharge.	1	
4415-0041	3" Deck Gun Discharge, Akron manual valve.	1	
4417-0106-165	Deck gun piping to be positioned centered in deck gun channel.	1	



Salescode	Extended Description	Qty	
<b>DISCHARGE OPTIONS</b>			
4417-0175	Innovative Controls push/pull valve controls with locking T handles.	1	
4417-0177	Innovative Controls 3/4" bleeder/drain valve include 1/4 turn T-handle.	7	
4417-0185	Innovative Controls discharge and intake bezels with integral color code and verbiage for side mount pump panel.	1	
<b>GAUGES</b>			
4435-0083	Innovative Controls 10 LED SL series water tank level gauge. On pump panel.	1	
4435-0178	Engine gauge package at the pump operator's panel.	1	
4435-0246	2.5" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel.	7	
4435-0247	4" Innovative Controls stainless steel case master pressure gauges with bezel. Intake 30-0-400, and discharge 0-400.	1	
<b>ELECTRICAL SYSTEMS</b>			
5010-0014-G97	Vehicle data recorder for commercial cab - 2009 NFPA compliant. Includes occupant detection with display. Display location: cab dash above transmission shift panel.	1	
5010-0036	V-MUX Electrical system for pumper / tanker / rescue.	1	
5010-0059-339	VFD Text display for V-MUX electrical system. Location: center of dash.	1	
<b>LIGHT BARS</b>			
5300-0021	Light bar Federal Signal JetSolaris 60" LED. Red Solaris reflectors with clear domes. NFPA compliant. Does not require 2 addl side facing bars. Location: Centered on the front cab roof.	1	
<b>WARNING LIGHT PACKAGES</b>			
5550-0055-534	Federal Signal QuadraFlare LED lower level warning light package. Includes (10) QL64XF-R LED light heads with bezels. Locate side facing lights: at forward most position, centered in rear wheel well, and on side of beavertail.	1	
5550-0067	Flash rate for Federal QuadraFlare LED lower level warning lights to be set at pattern 4, (75 QFPM).	1	
<b>WARNING LIGHTS</b>			
5600-0034-479-08	Federal model SV12FS Sentry (PR) with driver red, officer amber domes. Location: rear upper body on aerial style brackets.	1	
5600-0149-170	Hazard (door ajar) light, 2.5" incandescent. Location: center overhead.	1	
<b>DIRECTIONAL LIGHT BARS</b>			
5310-0025	Directional light circuit wiring through upper level warning.	1	



Salescode	Extended Description	Qty	
<b>SIRENS</b>			
5500-0009	Federal PA300 electronic siren recessed mounted.	1	
5500-0024-170	The electronic siren control is to be located on the center overhead.	1	
<b>SPEAKERS</b>			
5510-0029-209	Speaker, Federal Signal Dynamax ES100 with "E-ONE" grille through bumper. Location: driver side front bumper.	1	
<b>DOT LIGHTING</b>			
5150-0017	License plate light LED with chrome housing located at the rear of the body.	1	
5150-0022	Marker light LED body package. Commercial pumper bodies only.	1	
5150-0042	Federal Signal LED tail lights. Includes 4" diameter red LED stop/tail, amber turn and LED clear back-up.	1	
<b>LIGHTS - COMPARTMENT, STEP &amp; GROUND</b>			
5380-0008	Compartment light package incandescent for small bodies.	1	
5380-0027	Ground light package for cab and body - small.	1	
<b>LIGHTS - DECK AND SCENE</b>			
5390-0000-395	Deck light - Unity 12 volt (PR). Location: rear body/beavertail area on the trailing edge up high.	1	
5390-0001	Hose bed light Unity. Locate at front area of hose bed. Switched with work light switch in cab.	1	
5390-0005	Crosslay light deck Unity. Locate to rear of crosslay (SM) or forward of crosslay (TM).	1	
<b>LIGHTS - NON-WARNING</b>			
5400-0003	Engine compartment light (EA).	1	
5400-0010	Incandescent pump compartment light (EA).	1	
5400-0031	Pair of Cab Dome Large Lights mounted driver and officer side front. N/A on E-One Chassis. Required on Comm Chassis.	1	
5400-0047	Pump panel light package with (3) lights per side pump panel. Pump panels over 45" may require additional lights. Side mount only.	1	
<b>MISC ELECTRICAL</b>			
5110-0017	Back-up alarm 97 dB.	1	
<b>MISC LOOSE EQUIPMENT</b>			
7900-0014	DOT Required Drive Away Kit - Kit includes three (3) triangular warning reflectors with carrying case. This kit is for the end user and is to remain with the truck.	1	



Salescode	Extended Description	Qty	
<b>EXTERIOR PAINT</b>			
8100-0089	All applicable pump/pre-connect application modules are to have a sanded finish (not painted job color). Includes upper and lower pump modules, crosswalk module and/or speedlay/pre-connect module (as applicable). Rear mounted body/pump module to be painted job color.	1	
8100-0116	Rear body surface to have a sanded finish (not painted job color). Includes hinged doors that do not have discrete sales codes and removable panels.	1	
8100-0182-000-R5	Paint Body - Small - For Pumps, Rear Mounts, S/A Tankers/Weisides and Rescues. Sikkens paint. Color: FLNA3225 Red (Sikkens published).	1	
8100-0443-000-R5	Freightliner cab paint (by chassis OEM). Paint to match FLNA3225 Red (Sikkens published).	1	
<b>STRIPING</b>			
8300-0002-859-12	NFPA Scotchlite Stripe - 4" wide and straight on front/sides of cab and sides/rear of body. Color: White. Location: bottom of stripe flush with bottom of cab and straight back.	1	
8300-0042	White rubrail scotchlite insert.	1	
8300-0084-000-72	Chevron "A" style 6" printed sheet Scotchlite striping full width on rear of body. Includes rear facing extrusions, panels and doors. Colors to be Yellow/Red.	1	
8300-0313	Yellow line to indicate designated standing / walking areas above 48" high in compliance with 2016 NFPA 1901. Line to be 1" wide. Steps, ladders and areas with a railing or structure at least 12" high are excluded from requiring the line.	1	
<b>WARRANTY / STANDARD &amp; EXTENDED</b>			
9100-0000	Standard 1 Year Warranty.	1	
9100-0004	10 Year/100,000 Mile Structural Warranty for Alum Cab / Body - Statement of Warranty.	1	
9100-0005	10 Year Stainless Steel Plumbing Warranty - Statement of Warranty.	1	
9100-0019	10 Year Limited Paint and Perforation Warranty - For Sikkens Paint.	1	
<b>SUPPORT, DELIVERY, INSPECTIONS AND MANUALS</b>			
9300-0009	Manuals, Operator and Service CD-ROM.	1	
9300-0316	Fire Apparatus Safety Guide published by FAMA, latest edition.	1	
<b>Dealer Supplied Equipment</b>			