



Fire Apparatus Quotation for:
SUNBELT FIRE, INC



4-door Commercial Pumper

Quotation Number: 77429 Rev: 6

Unit Description: PMPR-COMM

Quote Description: Pumper, Commercial Chassis

Salesperson: DRHODES

| Salescode | Extended Description | Qty |
|-----------------------------|--|-----|
| TESTING COMPLIANCE STANDARD | | |
| 1001-0065 | The E-ONE supplied components of the vehicle shall meet the requirements of NFPA 1901, 2016 edition. | 1 |
| CHASSIS PREP | | |
| 1020-0010 | Comm Chassis Prep E-1 Supp-FL. | 1 |
| AXLE OPTIONS | | |
| 1025-0043 | Front axle for commercial chassis 14,000 lb. rating. | 1 |
| 1025-0046 | Rear axle for commercial chassis 23,000lb rating | 1 |
| TIRE OPTIONS | | |
| 1060-0117 | RWC AirGuard LED tire pressure monitoring valve stem caps (6) for single rear axle applications. | 1 |
| AIR SYSTEM OPTIONS | | |
| 1110-0010-277 | Air inlet. To charge brake system. Commercial chassis only. Location: driver's door step area. | 1 |
| 1110-0076 | Dual Stuttertone hood mounted air horns with driver and officer foot switches to be supplied and installed by Freightliner. | 1 |
| ENGINES & TRANSMISSIONS | | |
| 1200-0126 | Chassis speed to be electronic limited and not to exceed a maximum of 68 MPH. Note: Speed rating may be lower based on OEM tire ratings/top speed limitations provided on chassis. | 1 |
| 1200-0286 | Freightliner Cummins ISB 360 HP, 800 lb-ft Torque, 2013 EPA engine. | 1 |
| CHASSIS OPTIONS | | |
| 1680-0011 | Tow eyes rear below body, painted. | 1 |

| Salescode | Extended Description | Qty |
|----------------------------------|---|-----|
| CHASSIS OPTIONS | | |
| 1680-0078 | Tow hooks front OEM. Not available with extended E-ONE installed front bumper. Tow hooks are OEM supplied with chassis. | 1 |
| 1680-0104 | OEM chassis step package for Freightliner M2 series. Includes mounting plate for the battery charger receptacle and air inlet. | 1 |
| 1680-0235-R01 | The batteries to be located under left hand side of cab. | 1 |
| CAB MODEL | | |
| 1500-0009 | Four door Freightliner M2 106 4x2. | 1 |
| CAB BADGE PACKAGE | | |
| 1610-0000 | Cab and body to have applicable E-ONE logos. | 1 |
| CAB DOOR OPTIONS | | |
| 1550-0059-000-G6 | Reflective Red/Lemon Yellow printed striping positioned in the "A" formation located on the cab door panels. | 1 |
| MISC EXTERIOR CAB OPTIONS | | |
| 1675-0007 | Diesel fuel only label. | 1 |
| SEATS | | |
| 1685-0032 | Seating capacity tag of five occupants. | 1 |
| CAB ELECTRICAL OPTIONS | | |
| 1750-0059-277-04 | Receptacle inlet 20 amp with a Yellow cover. Location: driver's door step area. | 1 |
| 1750-0343 | Battery charger E-ONE LPC 20. 120 volt inlet, 20 amp output. | 1 |
| BODY COMPT LEFT SIDE | | |
| 3100-0094 | Driver side body with full height 30" wide forward and 36" wide rearward compartmentation. Includes (1) 56" wide compartment over the wheel well. | 1 |
| BODY COMPT RIGHT SIDE | | |
| 3120-0003 | Officer half side body with 30" wide forward and 36" wide rearward compartmentation. Includes adjustable ladder tracks. | 1 |
| BODY COMPT REAR | | |
| 3110-0005 | Full Height Rear Compartment. Includes smooth plate panels. | 1 |
| 3110-0034 | Upper rear compartment depth to be shallow. | 1 |
| 3340-0080 | Bolt-on diamond plate 18" tailboard (full width of body). Includes (2) squared off beaverails (no stanchions) with removable outer panels and handrails- (2) vertical on trailing edge of body and horizontal mounted handrail(s) below | 1 |

| Salescode | Extended Description | Qty |
|--------------------------------|---|-----|
| BODY COMPT REAR | | |
| | hosebed. | |
| DOORS | | |
| 3300-0007-003 | Door single vertical hinged painted. Location(s): L1 | 1 |
| 3300-0007-015 | Door single vertical hinged painted. Location(s): R1 | 1 |
| 3300-0011-004 | Door single horizontal hinged lift-up box pan configuration painted. Location(s): L2 | 1 |
| 3300-0164-016 | Door double vertical hinged w/rotary latches - painted . Location(s): R2 | 1 |
| 3300-0167-005 | Door double 3-point vertical hinged w/rotary latches - painted. Location(s): L3 | 1 |
| 3300-0169-027 | Door double 3-point vertical hinged w/rotary latches - smooth plate sanded. Location(s): B1 | 1 |
| COVERS | | |
| 3305-0007-000-13 | Vinyl Black hose bed cover with attached rear flap(s). | 1 |
| 3305-0008-000-13 | Vinyl Black crosslay cover with attached side flaps. | 1 |
| PUMP MODULE | | |
| 3130-0167 | Pump module to be 76" wide (side to side). Includes upper, lower, crosswalk, speedlay and tranverse module(s) if applicable. | 1 |
| 3130-0523 | Side mount pump module. Extruded aluminum with runningboards. | 1 |
| 3130-0532 | Pump panel opening is 39" wide. Pumper / tanker only. | 1 |
| 3130-0539 | Pump module height is 75". Pumper / tanker only. | 1 |
| PUMP PANELS | | |
| 3134-0016 | Stainless steel driver and officer side pump panels. | 1 |
| 3134-0143 | Officer side pump panel to be vertical hinged on forward extrusion. Panel to be (3) pieces with upper (2) panels secured in the closed position with push button latches. Upper panel to be held open with gas shock. | 1 |
| MISC PUMP PANEL OPTIONS | | |
| 4460-0003 | Pump panel tags color coded per NFPA compliance. | 1 |
| PUMP MODULE OPTIONS | | |
| 3136-0058 | E-ONE logo mounted one each side on pump module/preconnect panels. Logos to be sized as applicable to available space on panels. | 1 |
| 3136-0138 | Pump module storage pan. | 1 |
| 3136-0139 | Crosslay double 7.5" wide each to hold up to 200' of 2.0" DJ hose (each). | 1 |

| Salescode | Extended Description | Qty |
|-------------------------------|---|-----|
| WATER TANK | | |
| 4010-0099 | Fill tower(s) to be located offset to officer side of water tank. | 1 |
| 4010-0174 | 530 Gallon "I" Water Tank. UPF Poly III color fill towers. Note: Any foam cell(s) will reduce the overall water capacity. | 1 |
| TANK PLUMBING | | |
| 4450-0010 | 2" tank fill Akron manual valve. | 1 |
| 4450-0119 | 3" tank to pump Akron manual valve w/4" tank connection. | 1 |
| LADDER STORAGE / RACKS | | |
| 3365-0031 | Hard Suction Storage Rack. Officer side in adjustable track above ladders (if applicable). Includes spring hold downs and scuff plates. | 2 |
| 3365-0049 | Brand of ladders capable of being carried on unit to be Alco-Lite. | 1 |
| 3365-0087-C57 | The length of ladders capable of being stored shall be the following: 24' 2-section and 14' roof ladder. | 1 |
| HANDRAILS / STEPS | | |
| 3330-0277 | Innovative Controls dual lighted LED folding steps rear NFPA. Includes folding steps on driver side (staggered stepped as applicable with tailboard depth) for NFPA hosebed access and handrail mounted on driver side upper hosebed side (as applicable). | 1 |
| MISC BODY OPTIONS | | |
| 3000-0000 | Body mainframe and hosebed side assemblies for a 80" high body. | 1 |
| 3090-0002 | OAH. Unit has no overall height restrictions. | 1 |
| 3090-0004 | OAL. Unit has no overall length restrictions. | 1 |
| 3090-0007 | Hosebed hoseload allowance on the apparatus shall be 1200 lbs. | 1 |
| 3340-0004 | Hosebed above the booster tank. Includes forward hosebed and tower(s) cover plate work (as applicable). Hosebed adjustable divider extrusion rearward of the furthest tower is to run full width of the hosebed (as is practical with other hosebed mounted equipment). | 1 |
| 3340-0015 | Diamond plate single axle wheel well. Includes bolt-on composite wheel well liners and aluminum trim fenderettes. | 1 |
| 3340-0035 | Divider Long. To run full length of hose bed (front to rear). | 1 |
| 3340-0093 | Mud flaps, rear, black with E-ONE logo. | 1 |
| 3340-0110 | The rear of each hose bed divider to have a hand hold cut-out(s). | 1 |
| 3340-0145 | Rub rail for the body and pump area module(s). | 1 |
| 3340-0681 | Body mainframe layout line to be 24". Includes body and all applicable modules. | 1 |

| Salescode | Extended Description | Qty |
|-----------------------------------|---|-----|
| MISC BODY OPTIONS | | |
| 3340-1137-12B | Equipment allowance on the apparatus shall be 2000 lbs. This allowance is in addition to the weight of the hoses and ground ladders listed in the shop order as applicable. | 1 |
| PUMPS | | |
| 4005-0030 | Rating 1250 GPM | 1 |
| 4005-0195 | Hale QFLO 750-1250 GPM pump, single stage. Requires primer option. | 1 |
| PUMP CERTIFICATION | | |
| 4475-0000 | Pump certification 750-2250 GPM | 1 |
| PUMP OPTIONS | | |
| 4015-0029 | Hale pressure relief valve. | 1 |
| 4015-0037 | Engine throttle, vernier. | 1 |
| 4015-0053-198 | Steamers to be Flush + 1". Location: driver's side. | 1 |
| 4015-0053-199 | Steamers to be Flush + 1". Location: officer's side. | 1 |
| 4015-0098 | Manual operated master pump drain. The master drain shall be clearly marked and placed in accessible location on pump panel. | 1 |
| 4015-0238 | Hale electric primer (oil-less). | 1 |
| INTAKES | | |
| 4440-0005 | 2.5" Left Intake Akron Manual Valve. | 1 |
| INTAKE OPTIONS | | |
| 4445-0048 | Intake pressure relief valve, Task Force Tips. | 1 |
| DISCHARGES AND PRECONNECTS | | |
| 4415-0012-654 | 1.5" Crosslay with Akron manual valve. Location: crosslay 1 & 2. | 2 |
| 4415-0014-581 | 2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 1. | 1 |
| 4415-0014-582 | 2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 2. | 1 |
| 4415-0016-583 | 2.5" Right Pump Panel Discharge Akron Manual Valve. Location: right side discharge 1. | 1 |
| 4415-0022-350 | 2.5" Left Rear Discharge Akron Manual Valve. Location: left rear discharge. | 1 |
| 4415-0041 | 3" Deck Gun Discharge, Akron manual valve. | 1 |
| 4417-0106-165 | Deck gun piping to be positioned centered in deck gun channel. | 1 |

| Salescode | Extended Description | Qty |
|-------------------------------|--|-----|
| DISCHARGE OPTIONS | | |
| 4417-0175 | Innovative Controls push/pull valve controls with locking T handles. | 1 |
| 4417-0177 | Innovative Controls 3/4" bleeder/drain valve include 1/4 turn T-handle. | 7 |
| 4417-0185 | Innovative Controls discharge and intake bezels with integral color code and verbiage for side mount pump panel. | 1 |
| GAUGES | | |
| 4435-0083 | Innovative Controls 10 LED SL series water tank level gauge. On pump panel. | 1 |
| 4435-0178 | Engine gauge package at the pump operator's panel. | 1 |
| 4435-0246 | 2.5" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel. | 7 |
| 4435-0247 | 4" Innovative Controls stainless steel case master pressure gauges with bezel. Intake 30-0-400, and discharge 0-400. | 1 |
| ELECTRICAL SYSTEMS | | |
| 5010-0014-697 | Vehicle data recorder for commercial cab - 2009 NFPA compliant. Includes occupant detection with display. Display location: cab dash above transmission shift panel. | 1 |
| 5010-0036 | V-MUX Electrical system for pumper / tanker / rescue. | 1 |
| 5010-0059-339 | VFD Text display for V-MUX electrical system. Location: center of dash. | 1 |
| LIGHT BARS | | |
| 5300-0021 | Light bar Federal Signal JetSolaris 60" LED. Red Solaris reflectors with clear domes. NFPA compliant. Does not require 2 addl side facing bars. Location: Centered on the front cab roof. | 1 |
| WARNING LIGHT PACKAGES | | |
| 5550-0055-534 | Federal Signal QuadraFlare LED lower level warning light package. Includes (10) QL64XF-R LED light heads with bezels. Locate side facing lights: at forward most position, centered in rear wheel well, and on side of beavertail. | 1 |
| 5550-0067 | Flash rate for Federal QuadraFlare LED lower level warning lights to be set at pattern 4, (75 QFPM). | 1 |
| WARNING LIGHTS | | |
| 5600-0034-479-08 | Federal model SY12FS Sentry (PR) with driver red, officer amber domes. Location: rear upper body on aerial style brackets. | 1 |
| 5600-0149-170 | Hazard (door ajar) light, 2.5" incandescent. Location: center overhead. | 1 |
| DIRECTIONAL LIGHT BARS | | |
| 5310-0025 | Directional light circuit wiring through upper level warning. | 1 |

| Salescode | Extended Description | Qty |
|--|--|-----|
| SIRENS | | |
| 5500-0009 | Federal PA300 electronic siren recessed mounted. | 1 |
| 5500-0024-170 | The electronic siren control is to be located on the center overhead. | 1 |
| SPEAKERS | | |
| 5510-0029-209 | Speaker, Federal Signal Dynamax ES100 with "E-ONE" grille through bumper. Location: driver side front bumper. | 1 |
| DOT LIGHTING | | |
| 5150-0017 | License plate light LED with chrome housing located at the rear of the body. | 1 |
| 5150-0022 | Marker light LED body package. Commercial pumper bodies only. | 1 |
| 5150-0042 | Federal Signal LED tail lights. Includes 4" diameter red LED stop/tail, amber turn and LED clear back-up. | 1 |
| LIGHTS - COMPARTMENT, STEP & GROUND | | |
| 5380-0008 | Compartment light package incandescent for small bodies. | 1 |
| 5380-0027 | Ground light package for cab and body - small. | 1 |
| LIGHTS - DECK AND SCENE | | |
| 5390-0000-395 | Deck light - Unity 12 volt (PR). Location: rear body/beavertail area on the trailing edge up high. | 1 |
| 5390-0001 | Hose bed light Unity. Locate at front area of hose bed. Switched with work light switch in cab. | 1 |
| 5390-0005 | Crosslay light deck Unity. Locate to rear of crosslay (SM) or forward of crosslay (TM). | 1 |
| LIGHTS - NON-WARNING | | |
| 5400-0003 | Engine compartment light (EA). | 1 |
| 5400-0010 | Incandescent pump compartment light (EA). | 1 |
| 5400-0031 | Pair of Cab Dome Large Lights mounted driver and officer side front. N/A on E-One Chassis. Required on Comm Chassis. | 1 |
| 5400-0032 | Pair of Cab Dome Large Lights mounted driver and officer side Rear. N/A on E-One Chassis or two door commercial chassis. Required on Comm Chassis. | 1 |
| 5400-0047 | Pump panel light package with (3) lights per side pump panel. Pump panels over 45" may require additional lights. Side mount only. | 1 |
| MISC ELECTRICAL | | |
| 5110-0017 | Back-up alarm 97 dB. | 1 |
| MISC LOOSE EQUIPMENT | | |

| Salescode | Extended Description | Qty |
|---|---|-----|
| MISC LOOSE EQUIPMENT | | |
| 7900-0014 | DOT Required Drive Away Kit - Kit includes three (3) triangular warning reflectors with carrying case. This kit is for the end user and is to remain with the truck. | 1 |
| EXTERIOR PAINT | | |
| 8100-0089 | All applicable pump/pre-connect application modules are to have a sanded finish (not painted job color). Includes upper and lower pump modules, crosswalk module and/or speedlay/pre-connect module (as applicable). Rear mounted body/pump module to be painted job color. | 1 |
| 8100-0116 | Rear body surface to have a sanded finish (not painted job color). Includes hinged doors that do not have discrete sales codes and removable panels. | 1 |
| 8100-0182-000-R5 | Paint Body - Small - For Pumps, Rear Mounts, S/A Tankers/Wetsides and Rescues. Sikkens paint. Color: FLNA3225 Red (Sikkens published). | 1 |
| 8100-0443-000-R5 | Freightliner cab paint (by chassis OEM). Paint to match FLNA3225 Red (Sikkens published). | 1 |
| STRIPING | | |
| 8300-0002-859-12 | NFPA Scotchlite Stripe - 4" wide and straight on front/sides of cab and sides/rear of body. Color: White. Location: bottom of stripe flush with bottom of cab and straight back. | 1 |
| 8300-0042 | White rubrail scotchlite insert. | 1 |
| 8300-0084-000-72 | Chevron "A" style 6" printed sheet Scotchlite striping full width on rear of body. Includes rear facing extrusions, panels and doors. Colors to be Yellow/Red. | 1 |
| 8300-0313 | Yellow line to indicate designated standing / walking areas above 48" high in compliance with 2016 NFPA 1901. Line to be 1" wide. Steps, ladders and areas with a railing or structure at least 12" high are excluded from requiring the line. | 1 |
| WARRANTY / STANDARD & EXTENDED | | |
| 9100-0000 | Standard 1 Year Warranty. | 1 |
| 9100-0004 | 10 Year/100,000 Mile Structural Warranty for Alum Cab / Body - Statement of Warranty. | 1 |
| 9100-0005 | 10 Year Stainless Steel Plumbing Warranty - Statement of Warranty. | 1 |
| 9100-0019 | 10 Year Limited Paint and Perforation Warranty - For Sikkens Paint. | 1 |
| SUPPORT, DELIVERY, INSPECTIONS AND MANUALS | | |
| 9300-0009 | Manuals, Operator and Service CD-ROM. | 1 |
| 9300-0316 | Fire Apparatus Safety Guide published by FAMA, latest edition. | 1 |

| Salescode | Extended Description | Qty |
|---------------------------|----------------------|-----|
| Dealer Supplied Equipment | | |
| | | |