



Fire Apparatus Quotation for:
SUNBELT FIRE, INC
137' Rear Mount Aerial



Quotation Number: 77705 Rev: 10

Unit Description: AERM-CYC2-137L

Quote Description: Aerial Rear Mount, Cyclone II, 137 Foot Ladder

Salesperson: DRHODES

| Salescode | Extended Description | Qty |
|------------------------------------|--|-----|
| TESTING COMPLIANCE STANDARD | | |
| 1001-0065 | The E-ONE supplied components of the vehicle shall meet the requirements of NFPA 1901, 2016 edition. | 1 |
| BUMPERS | | |
| 1160-0000 | Bumper 10" stainless steel. | 1 |
| 1160-0011 | 4" Front Bumper Extension. | 1 |
| FRAME ASSEMBLY | | |
| 1250-0005 | Frame - Torque box for tandem axle RM aerial. | 1 |
| AXLE OPTIONS | | |
| 1025-0013 | Meritor FL-943 front axle 21,500 lbs. | 1 |
| 1025-0023 | Meritor RT-50-160 rear tandem axle 54,000 lb. capacity. | 1 |
| 1025-0028 | Koni shock absorbers for front axle - adjustable. | 1 |
| SUSPENSIONS | | |
| 1070-0002 | Rear suspension springs rated equal to the capacity of the axles. | 1 |
| WHEEL OPTIONS | | |
| 1050-0007 | Front axle wheel trim kit. Includes stainless steel lug nut covers (chrome plated plastic if applicable) and center cap with E-ONE logo. Note: Center cap will have an inspection port IPO a logo if equipped with Stemco oil seals. | 1 |
| 1050-0009 | Rear axle (tandem) wheel trim kit. Includes stainless steel lug nut covers (chrome plated plastic if applicable) and center caps with E-ONE logo. E-ONE custom chassis w/steel wheels will have chrome plated plastic lug covers. | 1 |
| 1050-0044 | Accuride aluminum wheels for front axle (2). | 1 |
| 1050-0046 | Accuride aluminum wheels for rear axles (8). | 1 |

| Salescode | Extended Description | Qty |
|------------------------------------|--|-----|
| TIRE OPTIONS | | |
| 1060-0008 | Eight Michelin 12R tires model XZE for rear axles | 1 |
| 1060-0046 | Two Michelin 425 tires model XFE for front axle. | 1 |
| 1060-0119 | RWC AirGuard LED tire pressure monitoring valve stem caps (10) for tandem rear axle applications. | 1 |
| BRAKE SYSTEMS | | |
| 1100-0000 | 16-1/2" x 6" S-cam brakes with ArvinMeritor automatic slack adjusters for front axle. | 1 |
| 1100-0006 | Parking brake release mounted on the driver's side lower dash. | 1 |
| 1100-0008 | Brake system air 6X4. | 1 |
| 1100-0014 | ArvinMeritor 16-1/2" x 7" S-cam brakes with cast brake drums for a tandem rear axle. | 1 |
| 1100-0026 | G4 Electronic Stability Control (6x4). Includes RSC and ATC. Not available on 6x6 or commercial chassis. | 1 |
| AIR SYSTEM OPTIONS | | |
| 1110-0000-001 | Inlet for air system. Location: driver door jamb. | 1 |
| 1110-0002 | Air dryer Bendix AD-9. | 1 |
| 1110-0006 | Air lines nylon. | 1 |
| 1110-0041 | Air horns Grover recessed in bumper (PR). | 1 |
| ENGINES & TRANSMISSIONS | | |
| 1200-0017 | Push-button transmission shift selector. | 1 |
| 1200-0021 | TransSynd synthetic transmission fluid for EVS 4000. | 1 |
| 1200-0096 | Electronic speed limiting set at 60 MPH. | 1 |
| 1200-0317 | Eng/Trans Cummins ISX12 500HP with EVS4000 transmission. 2016 EPA Compliant. | 1 |
| SECONDARY BRAKING | | |
| 1125-0002 | Jacobs engine compression brake. | 1 |
| 1125-0023 | Transmission to seek second gear when Jacobs engine brake or Telma retarder is engaged. N/A with Trans retarder. | 1 |
| COOLING PACKAGE | | |
| 1800-0013 | Cooling system for use with Cyclone II X, Typhoon X, and Quest chassis. For use with 2010 / 2013 / 2016 EPA engines. Includes coolant recovery system. | 1 |
| FUEL SYSTEMS | | |

| Salescode | Extended Description | Qty |
|--------------------------|---|-----|
| FUEL SYSTEMS | | |
| 1350-0004 | Fuel system 50 gallon saddle tanks. | 1 |
| 1350-0022 | Fuel line hose rubber. | 1 |
| ALTERNATOR | | |
| 1700-0005 | Alternator Leece Neville 320 amp. 320 amp SAE/275 amp NEPA. | 1 |
| BATTERIES | | |
| 1400-0002 | Battery four group 31 1000 CCA. | 1 |
| CHASSIS OPTIONS | | |
| 1680-0005 | Thermatic fan clutch. | 1 |
| 1680-0007 | Drivelines 1810. Required on 1550 lb/ft torque or greater engines. | 1 |
| 1680-0008 | Tow eyes front painted below bumper/cab (PR). | 1 |
| 1680-0012 | Tow eyes rear frame painted. | 1 |
| 1680-0017 | Hotshift PTO. | 1 |
| 1680-0188 | Aerial hydraulics installed on bottom port of EVS4000/4500 transmission (to allow for flat rear cab floor). Requires drive through hyd pump option (6150-0015) on aerials with hyd generator. | 1 |
| 1680-0250-M58 | Diesel Exhaust Fluid (DEF) 5 gallon tank for 2013 / 2016 EPA engines. Location: left side below rear of cab. | 1 |
| 1680-0284 | Radiator mounted power steering cooler. | 1 |
| CAB MODEL | | |
| 1520-0008 | Cyclone II X medium cab with 58" CA | 1 |
| CAB ROOF TYPE | | |
| 1615-0004 | Cab roof to be "flat" with trough for waterway. Required with HM100 (with waterway), HP100 (all), CR100/92 Pltrm (SdStckr and W/O/P) or HP100 Pltrm (all). | 1 |
| CAB BADGE PACKAGE | | |
| 1610-0000 | Cab and body to have applicable E-ONE logos. | 1 |
| CAB DOOR OPTIONS | | |
| 1550-0003 | Rear crew cab doors in the medium position. | 1 |
| 1550-0006 | Driver and officer cab door windows. Include rear fixed window. | 1 |
| 1550-0013 | Driver and Officer door windows. Includes electric roll-down actuation. Each door to have individual control at door position and the driver door is to have master | 1 |

| Salescode | Extended Description | Qty |
|----------------------------------|---|-----|
| CAB DOOR OPTIONS | | |
| | control for all power window locations. | |
| 1550-0014 | Rear crew cab door windows. Includes electric roll-down actuation. Each door to have individual control. Not available with paddle style door latching. | 1 |
| 1550-0016 | Cab door panels ABS. | 1 |
| 1550-0025 | All cab doors shall have "L" style exterior latches. | 1 |
| 1550-0037-659 | (4) Incandescent cab step area lighting. Locate each light in on each cab door in the inboard position. Lights to be switched with door ajar. | 1 |
| 1550-0044 | All cab door kick plates to be made from diamond plate aluminum. | 1 |
| 1550-0059-000-G6 | Reflective Red/Lemon Yellow printed striping positioned in the "A" formation located on the cab door panels. | 1 |
| 1550-0077 | Interior cab door locks - manual. Will have manual actuation from each respective door. Includes barrel style key lock on each exterior cab door. | 1 |
| 1550-0084 | All cab exterior access doors to have 1250 keyed locks. | 1 |
| MIRRORS | | |
| 1670-0018 | Velvac mirrors model 2025 with LED directional arrows. Door mounted (bottom mount) with remote control and heat. | 1 |
| MISC EXTERIOR CAB OPTIONS | | |
| 1550-0020 | Windows cab side fixed driver's side. | 1 |
| 1550-0033 | Windows cab side fixed officer's side. | 1 |
| 1675-0022 | Pair of 18" handrails located just behind driver and officer front door one each side. | 1 |
| 1675-0023 | Pair of 18" handrails located just behind driver and officer rear door (ALS doors if equipped) one each side. | 1 |
| 1675-0030 | Mud flaps, front, black with E-ONE logo. | 1 |
| 1675-0047 | Rear cab wall to be 3/16" aluminum diamond plate. | 1 |
| 1675-0201 | Large radius cab wheel well. Includes bolt-on adjustable wheel well trim. | 1 |
| 1675-0202 | Mounting plate for battery charger receptacle, indicator and air inlet (if applicable). Plate to be removable brushed stainless steel. | 1 |
| HVAC | | |
| 1515-0018 | Air conditioning for the Typhoon X, CII X and Quest with roof top mounted condenser. | 1 |
| 1515-0053 | Controls for heating and air conditioning shall be located in the center dash area. (Lower area on Typhoon and CII with severe duty dash) | 1 |

| Salescode | Extended Description | Qty |
|----------------------------------|---|-----|
| SEATS | | |
| 1510-0003 | Seats, Inc. brand 911 cab seats. | 1 |
| 1510-0005 | Seat cover material Imperial 1200. | 1 |
| 1510-0008 | Seat color gray. | 1 |
| 1510-0035-147 | Universal air pack bottle bracket (EA). Location: officer's seat. | 1 |
| 1510-0035-148 | Universal air pack bottle bracket (EA). Location: rear facing driver's side. | 1 |
| 1510-0035-215 | Universal air pack bottle bracket (EA). Location: rear facing officer's side. | 1 |
| 1510-0038 | Driver seat 911 air ride. | 1 |
| 1510-0042 | Officer seat to be 911 fixed SCBA. | 1 |
| 1510-0050 | Rear facing 911 seat with SCBA driver's side. | 1 |
| 1510-0053 | Rear facing 911 seat with SCBA officer's side. | 1 |
| 1685-0031 | Seating capacity tag of four occupants. | 1 |
| MISC INTERIOR CAB OPTIONS | | |
| 1685-0000 | Cab interior gray. Does not include engine cover or seat color. | 1 |
| 1685-0005 | Lexan sun visors, driver and officer's side overhead. | 1 |
| 1685-0168 | ABS Dash package. Includes center and officer side dash, lower kick panels and "A" post covers. | 1 |
| 1685-0187 | Severe duty engine cover, molded polyurethane. | 1 |
| CAB ELECTRICAL OPTIONS | | |
| 1750-0046-195 | Cab Headlights. Position: lower. | 1 |
| 1750-0059-179-04 | Receptacle inlet 20 amp with a Yellow cover. Location: outside driver's door next to handrail. | 1 |
| 1750-0075 | English dominant main cab gauge cluster. | 1 |
| 1750-0083-172 | Turn signal Federal Signal QuadraFlare QL64Z-ARROW LED amber pair located upper headlight bezel. | 1 |
| 1750-0198-A31 | Battery charger to be located behind driver's seat. | 1 |
| 1750-0343 | Battery charger E-ONE LPC 20. 120 volt inlet, 20 amp output. | 1 |
| 1750-0435 | Halogen cab headlights. TyphoonX, CITX and QST2 only. | 1 |
| 1750-0449 | Momentary DPF regeneration override switch. | 1 |
| 1750-0451 | Steering wheel with switch pods IPQS. Includes wiper functions, master warning sw, air horn sw, aux brake on/off and (3) aux switches. For use only with Typhoon and CII NOT equipped with 4Front. (Requires separate programming options to activate aux switches) | 1 |

| Salescode | Extended Description | Qty |
|-------------------------------|---|-----|
| CAB ELECTRICAL OPTIONS | | |
| 5400-0037 | Dome Lts Red/White Incandescent. Package includes two lights mounted in the front and two mounted in the rear of the cab. White light wire through door and light assembly mounted switch. Red light through light assembly mounted switch. | 1 |
| BODY SPEC | | |
| 3090-0000 | Body Specs - SideStacker aerial with tandem axle. Includes left rear staircase with pocket style drop down step. | 1 |
| BODY COMPT REAR | | |
| 3110-0360 | Rear of body to have un-painted smooth plate overlay style body panels to facilitate rear body striping. | 1 |
| AERIAL BODY OPTIONS | | |
| 3310-0002 | Compartments driver side CR100/95 platform SideStacker with 300g tank. Includes rescue style compartments. | 1 |
| 3310-0013 | Compartments officer side CR100/95 platform SideStacker with 300g tank. Includes rescue style compartments ahead of wheel wells with standard hoses. | 1 |
| 3310-0032 | Recessed tubes for (6) pike poles. Not available on HP75 SideStacker. | 1 |
| 3310-0051 | Crosslay double to hold up to 200' of 2.0" DJ (each). Includes storage pan to rear of crosslays. | 1 |
| 3310-0069 | Rear ladder tunnel doors. Vertically hinged smooth plate to match rear body finish. | 1 |
| 3310-0162 | Jack leg opening covers diamond plate (4) sets. Includes diamond plate outrigger covers and fixed diamond plate filler panels. HM100/110 requires surface mount warning lights. | 1 |
| 3310-0303 | Auxiliary Jack pad 24X24 (4) with 20 degree formed handle. Includes (4) mounting brackets. | 1 |
| DOORS | | |
| 3300-0007-017 | Door single vertical hinged painted. Location(s): R3 | 1 |
| 3300-0007-018 | Door single vertical hinged painted. Location(s): R4 | 1 |
| 3300-0011-005 | Door single horizontal hinged lift-up box pan configuration painted. Location(s): L3 | 1 |
| 3300-0011-006 | Door single horizontal hinged lift-up box pan configuration painted. Location(s): L4 | 1 |
| 3300-0017-003 | Door roll up short (up to 45") with satin finish ROM. Location(s): L1. | 1 |

| Salescode | Extended Description | Qty |
|--------------------------------|--|-----|
| DOORS | | |
| 3300-0017-007 | Door roll up short (up to 45") with satin finish ROM. Location(s): L5. | 1 |
| 3300-0017-015 | Door roll up short (up to 45") with satin finish ROM. Location(s): R1. | 1 |
| 3300-0019-004 | Door roll up tall (greater than 45") with satin finish ROM. Location(s): L2. | 1 |
| 3300-0019-008 | Door roll up tall (greater than 45") with satin finish ROM. Location(s): L6. | 1 |
| 3300-0019-016 | Door roll up tall (greater than 45") with satin finish ROM. Location(s): R2. | 1 |
| COVERS | | |
| 3305-0007-000-13 | Vinyl Black hose bed cover with attached rear flap(s). | 1 |
| 3305-0008-000-13 | Vinyl Black crosslay cover with attached side flaps. | 1 |
| PUMP PANELS | | |
| 3134-0016 | Stainless steel driver and officer side pump panels. | 1 |
| 3134-0055 | Officer side upper pump access panel to be horizontal hinged with stainless steel door. Includes (2) push button latches and (2) hold open devices. | 1 |
| MISC PUMP PANEL OPTIONS | | |
| 4460-0003 | Pump panel tags color coded per NFPA compliance. | 1 |
| WATER TANK | | |
| 4010-0195 | 300 gallon "T" water tank. UPF Poly III blue fill tower. | 1 |
| TANK PLUMBING | | |
| 4450-0010 | 2" tank fill Akron manual valve. | 1 |
| 4450-0022 | 3" tank to pump Akron manual valve. | 1 |
| LADDER STORAGE / RACKS | | |
| 3365-0013-607 | Center mounted ladder tunnel. Ladder rack to hold: (2)PEL-35, PEL-28, PEL-24, PRL-20, PRL-16 and FL-10 (with rubber block feet). | 1 |
| HANDRAILS / STEPS | | |
| 3330-0002-050 | Slide-out platform, rollerless. Includes chrome grab handle centered on the front face of the platform (includes hand rail as applicable). Located below driver side pump panel. | 1 |
| MISC BODY OPTIONS | | |
| 3090-0001 | Hosebed hoselod allowance on the apparatus shall be 1000 lbs. | 1 |
| 3090-0002 | GAH. Unit has no overall height restrictions. | 1 |
| 3090-0004 | OAL. Unit has no overall length restrictions. | 1 |

| Salescode | Extended Description | Qty |
|-----------------------------------|---|-----|
| MISC BODY OPTIONS | | |
| 3340-0093 | Mud flaps, rear, black with E-ONE logo. | 1 |
| 3340-0107 | Diamond plate tandem axle wheel well. Includes bolt-on composite wheel well liners and fenderettes. | 1 |
| 3340-0270 | The painted aerial body side panels shall be smooth / flush. Applies to SideStacker HB side, panels next to water tank on MM, and upper body sides on RLP. | 1 |
| 3340-1137-12C | Equipment allowance on the apparatus shall be 2500 lbs. This allowance is in addition to the weight of the hoses and ground ladders listed in the shop order as applicable. | 1 |
| PUMPS | | |
| 4005-0031 | Rating 1500 GPM. | 1 |
| 4005-0196 | Hale QMAX 1000-2250 GPM single stage pump. Requires primer option. | 1 |
| PUMP CERTIFICATION | | |
| 4475-0000 | Pump certification 750-2250 GPM | 1 |
| PUMP OPTIONS | | |
| 4015-0029 | Hale pressure relief valve. | 1 |
| 4015-0037 | Engine throttle, vernier. | 1 |
| 4015-0038 | Pump seal packing for Hale pump. | 1 |
| 4015-0053-198 | Steamers to be Flush + 1". Location: driver's side. | 1 |
| 4015-0053-199 | Steamers to be Flush + 1". Location: officer's side. | 1 |
| 4015-0073 | Manual operated master pump drain. The master drain shall be clearly marked and placed in accessible location below running board on driver side or L1 compartment. | 1 |
| 4015-0210 | Pump cooler with Innovative Control 1/4 turn valve with "T" handle and label. | 1 |
| 4015-0238 | Hale electric primer (oil-less). | 1 |
| INTAKES | | |
| 4440-0005 | 2.5" Left Intake Akron Manual Valve. | 1 |
| INTAKE OPTIONS | | |
| 4445-0009 | Intake relief valve, Akron. | 1 |
| DISCHARGES AND PRECONNECTS | | |
| 4415-0012-654 | 1.5" Crosslay with Akron manual valve. Location: crosslay 1 & 2. | 2 |

| Salescode | Extended Description | Qty |
|-----------------------------------|---|-----|
| DISCHARGES AND PRECONNECTS | | |
| 4415-0014-581 | 2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 1. | 1 |
| 4415-0014-582 | 2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 2. | 1 |
| 4415-0016-583 | 2.5" Right Pump Panel Discharge Akron Manual Valve. Location: right side discharge 1. | 1 |
| 4415-0016-584 | 2.5" Right Pump Panel Discharge Akron Manual Valve. Location: right side discharge 2. | 1 |
| 4415-0051 | 4" Waterway Discharge with 3" Akron Manual Valve. | 1 |
| DISCHARGE OPTIONS | | |
| 4417-0175 | Innovative Controls push/pull valve controls with locking T handles. | 1 |
| 4417-0176 | Innovative Controls 3/4" bleeder/drain valve include lift lever with ergonomic grip. | 7 |
| 4417-0185 | Innovative Controls discharge and intake bezels with integral color code and verbiage for side mount pump panel. | 1 |
| GAUGES | | |
| 4435-0069 | Class 1 ENFO IV system on pump operator's panel. | 1 |
| 4435-0083 | Innovative Controls 10 LED SL series water tank level gauge. On pump panel. | 1 |
| 4435-0246 | 2.5" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel. | 7 |
| 4435-0247 | 4" Innovative Controls stainless steel case master pressure gauges with bezel. Intake 30-0-400, and discharge 0-400. | 1 |
| ELECTRICAL SYSTEMS | | |
| 5010-0039 | V-MUX Electrical system for aeriels. | 1 |
| 5010-0049 | Vehicle data recorder - 2009 / 2016 NFPA compliant. Includes occupant detection shown in multiplex display. E-ONE chassis only. | 1 |
| 5010-0055-649 | Vista IV display for V-MUX electrical system. Location: driver's side engine cover. | 1 |
| LIGHT BARS | | |
| 5300-0015-035 | Light bars Federal Signal ADX2201 LED (PR) with red lenses. Location: front cab corners at 20 degree angle. | 1 |
| WARNING LIGHT PACKAGES | | |
| 5550-0067 | Flash rate for Federal QuadraFlare LED lower level warning lights to be set at pattern 4, (75 QPPM). | 1 |

| Salescode | Extended Description | Qty |
|--|---|-----|
| WARNING LIGHT PACKAGES | | |
| 5550-0192-538 | Federal Signal QuadraFlare LED lower level warning light package. Includes (8) QL64x4-R LED light heads with bezels and (2) IMPAXX LED model IPX302-4 light heads. Locate side facing lights: at forward most position, in rear wheel well offset to front, and side facing at rear of body in rubrail if equipped. | 1 |
| WARNING LIGHTS | | |
| 5600-0034-479-09 | Federal model SY12FS Sentry (PR) with driver amber, officer red domes. Location: rear upper body on aerial style brackets. | 1 |
| 5600-0149-170 | Hazard (door ajar) light, 2.5" Incandescent. Location: center overhead. | 1 |
| DIRECTIONAL LIGHT BARS | | |
| 5310-0025 | Directional light circuit wiring through upper level warning. | 1 |
| SIRENS | | |
| 5500-0009 | Federal PA300 electronic siren recessed mounted. | 1 |
| 5500-0024-170 | The electronic siren control is to be located on the center overhead. | 1 |
| SPEAKERS | | |
| 5510-0029-209 | Speaker, Federal Signal Dynamax ES100 with "E-ONE" grille through bumper. Location: driver side front bumper. | 1 |
| DOT LIGHTING | | |
| 5150-0017 | License plate light LED with chrome housing located at the rear of the body. | 1 |
| 5150-0026 | Marker light LED body/cab package. E-ONE custom cab with aerial ladder, Mid-Mount platform or Bronco bodies only. | 1 |
| 5150-0059 | Federal Signal QuadraFlare LED vertical mount tail lights. Includes LED stop/tail, arrow turn and back-up lights with vertical Cast 3 housing and weatherproof connectors. | 1 |
| LIGHTS - COMPARTMENT, STEP & GROUND | | |
| 5380-0010 | Compartment light package incandescent for large bodies. | 1 |
| 5380-0027 | Ground light package for cab and body - small. | 1 |
| 5380-0033 | Step light package body - small. | 1 |
| LIGHTS - DECK AND SCENE | | |
| 5390-0000-444 | Deck light - Unity 12 volt (PR). Location: (1) each side over rear ladder tunnel. | 1 |
| 5390-0001 | Hose bed light Unity. Locate at front area of hose bed. Switched with work light switch in cab. | 1 |

| Salescode | Extended Description | Qty |
|--|---|-----|
| LIGHTS - DECK AND SCENE | | |
| 5390-0005 | Crosslay light deck Unity. Locate to rear of crosslay (SM) or forward of crosslay (TM). | 1 |
| LIGHTS - NON-WARNING | | |
| 5400-0003 | Engine compartment light (EA). | 1 |
| 5400-0010 | Incandescent pump compartment light (EA). | 1 |
| 5400-0047 | Pump panel light package with (3) lights per side pump panel. Pump panels over 45" may require additional lights. Side mount only. | 1 |
| CONTROLS / SWITCHES | | |
| 5100-0000-198 | Foot switch to control air horns located driver's side. | 1 |
| 5100-0000-199 | Foot switch to control air horns located officer's side. | 1 |
| CAMERAS / INTERCOM | | |
| 5350-0156 | FRC ACT 2-way aerial intercom. | 1 |
| MISC ELECTRICAL | | |
| 5110-0017 | Back-up alarm 97 dB. | 1 |
| AERIAL MODEL | | |
| 6100-0034 | Ladder CR137 SideStacker with waterway to 110'. Includes left side console with cover, turntable mansaver bars, split steps at tip and jack leg flood lights. | 1 |
| AERIAL HYDRAULIC SYSTEM OPTIONS | | |
| 6150-0003-216 | Gauge aerial hydraulic oil level. Electronic display to be located on pump operator's panel. | 1 |
| AERIAL CONTROLS | | |
| 6850-0026 | Direct hydraulic aerial control system. | 1 |
| MONITORS | | |
| 6300-0016 | Monitor TFT electric 1000 GPM for ladder with a powder coated silver finish. Includes tip and base controls. | 1 |
| AERIAL WARNING LIGHTS | | |
| 6550-0000 | Outrigger warning lights (4). Trucklite Model 60015R. | 1 |
| AERIAL LIGHTING | | |
| 6560-0004-231 | Collins light FX-12 located left side tip. | 1 |
| 6560-0032 | Locate spot, flood and /or quartz lights on ladder fly section as far back from tip | 1 |

| Salescode | Extended Description | Qty |
|-----------------------------|--|-----|
| AERIAL LIGHTING | | |
| 6560-0041 | as possible. Whelen LED model PFBP12C at base (PR). | 1 |
| WATERWAY OPTIONS | | |
| 6350-0005 | Rear 4" NST waterway inlet for rear mounted aerials. Includes chrome cap. | 1 |
| 6350-0010 | Flowrinder with single readout and totalizer for the aerial waterway to be located at the aerial control station. | 1 |
| 6350-0067 | 2.5" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel. Locate next to waterway inlet. | 1 |
| SIGN PLATES | | |
| 6750-0002-000-39 | Aerial sign plates 22 x 144 (PR). Available on HM100, HM110, 95, CR100 and CR137 only. Does not include lettering. Color: Job Color. | 1 |
| AERIAL TESTING | | |
| 6900-0000 | Aerial flow test - 3rd party. | 1 |
| 6900-0007 | Aerial 2016 NFPA Certification. | 1 |
| ELBOWS | | |
| 7400-0005 | Chrome discharge elbow 2.5", 45 degree. | 4 |
| GROUND LADDERS | | |
| 7800-0002 | Alco-Lite FL-10, 10' folding ladder without shoes. | 1 |
| 7800-0010 | Alco-Lite PRL-16' roof ladder. | 1 |
| 7800-0016 | Alco-Lite PEL-24' 2-section extension ladder. | 1 |
| 7800-0021 | Alco-Lite PEL-28' extension ladder. | 1 |
| 7800-0024 | Alco-Lite PEL-35' extension ladder. | 2 |
| 7800-0038 | Alco-Lite PRL-20' roof ladder. | 1 |
| MISC LOOSE EQUIPMENT | | |
| 7900-0014 | DOT Required Drive Away Kit - Kit includes three (3) triangular warning reflectors with carrying case. This kit is for the end user and is to remain with the truck. | 1 |
| EXTERIOR PAINT | | |
| 8100-0084 | All applicable pump/pre-connect application modules are to have a job color finish. Includes upper and lower pump modules, crosswalk module and/or speedlay/pre-connect module (as applicable). Rear mounted body/pump module to be painted job color. | 1 |

| Salescode | Extended Description | Qty |
|---|---|-----|
| EXTERIOR PAINT | | |
| 8100-0116 | Rear body surface to have a sanded finish (not painted job color). Includes hinged doors that do not have discrete sales codes and removable panels. | 1 |
| 8100-0176-000-17 | Paint E-ONE chassis cab - Sikkens paint. Color: FLNA3225E-1 Red. | 1 |
| 8100-0183-000-17 | Paint Body - Large - For Aerials, T/A Tankers/Wetstides, Rear Mounts and Rescues. Sikkens paint. Color: FLNA3225E-1 Red. | 1 |
| 8100-0354 | Paint lift cylinders, extension cylinders and upper turntable steelwork primary job color (does not apply to TT deck). | 1 |
| INTERIOR PAINT | | |
| 8150-0011 | The interior of the cab to be painted Zolatone gray. | 1 |
| STRIPING | | |
| 8200-0016 | White reflective tape on (4) outriggers. | 1 |
| 8300-0003-334-12 | NFPA Scotchlite Stripe - 6" wide and straight on front/sides of cab and sides/rear of body. Color: White. Location: bottom of stripe flush with top of bumper and straight back. | 1 |
| 8300-0042 | White rubrail scotchlite insert. | 1 |
| 8300-0123-000-72 | Chevron "A" style 6" printed pattern NFPA Scotchlite striping. Provided to driver and officer rear compartment face, smooth plate panels and/or doors outboard and above the center rear compartment opening and the vertical hosebed extrusions (terminate just above the upper hand rail stanchion). The vertical and horizontal extrusions inboard of the vertical hose bed extrusions shall remain visible with a sanded finish. Colors to be Yellow/Red. | 1 |
| 8300-0313 | Yellow line to indicate designated standing / walking areas above 48" high in compliance with 2016 NFPA 1901. Line to be 1" wide. Steps, ladders and areas with a railing or structure at least 12" high are excluded from requiring the line. | 1 |
| GRAPHICS | | |
| 8400-0022 | Logo E-ONE (PR) on aerial lift cylinder. Logo to be black and white reflective material approx 14" long located midway along outward surface of cylinder. | 1 |
| WARRANTY / STANDARD & EXTENDED | | |
| 9100-0000 | Standard 1 Year Warranty. | 1 |
| 9100-0003 | Lifetime Frame Warranty. | 1 |
| 9100-0004 | 10 Year/100,000 Mile Structural Warranty for Alum Cab / Body - Statement of Warranty. | 1 |
| 9100-0005 | 10 Year Stainless Steel Plumbing Warranty - Statement of Warranty. | 1 |
| 9100-0007 | 20 Year Aerial Device Structural Warranty - Integrity Limited Warranty. | 1 |

| Salescode | Extended Description | Qty |
|---|---|-----|
| WARRANTY / STANDARD & EXTENDED | | |
| 9100-0019 | 10 Year Limited Paint and Perforation Warranty - For Sikkens Paint. | 1 |
| SUPPORT, DELIVERY, INSPECTIONS AND MANUALS | | |
| 9300-0000 | Vehicle familiarization aerial (Domestic). | 1 |
| 9300-0009 | Manuals, Operator and Service CD-ROM. | 1 |
| 9300-0016 | Approval Drawings-Standard. | 1 |
| 9300-0316 | Fire Apparatus Safety Guide published by FAMA, latest edition. | 1 |
| Dealer Supplied Equipment | | |
| | | |