



Fire Apparatus Quotation for:
SUNBELT FIRE, INC



2-door Commercial Water Tender

Quotation Number: 77426 Rev: 4

Unit Description: WTSA-COMM

Quote Description: Tanker, Wetside, Single Axle, Aluminum

Salesperson: DRHODES

Salescode	Extended Description	Qty
TESTING COMPLIANCE STANDARD		
1001-0065	The E-ONE supplied components of the vehicle shall meet the requirements of NFPA 1901, 2016 edition.	1
CHASSIS PREP		
1020-0010	Comm Chassis Prep E-1 Supp-FL.	1
1020-0047	Engine cooler. For use with commercial chassis - supplied by chassis OEM. Requires pump cooler valve on pump panel.	1
TIRE OPTIONS		
1060-0117	RWC AirGuard LED tire pressure monitoring valve stem caps (6) for single rear axle applications.	1
AIR SYSTEM OPTIONS		
1110-0010-277	Air inlet. To charge brake system. Commercial chassis only. Location: driver's door step area.	1
ENGINES & TRANSMISSIONS		
1200-0137	Electronic speed limiting set to 60 MPH.	1
1200-0257	Freightliner Cummins ISL 350 HP 2013 EPA engine.	1
CHASSIS OPTIONS		
1680-0011	Tow eyes rear below body, painted.	1
1680-0078	Tow hooks front OEM. Not available with extended E-ONE installed front bumper. Tow hooks are OEM supplied with chassis.	1
1680-0104	OEM chassis step package for Freightliner M2 series. Includes mounting plate for the battery charger receptacle and air inlet.	1
CAB MODEL		
1520-0085	Freightliner M2 106 two door cab.	1

Salescode	Extended Description	Qty
CAB BADGE PACKAGE		
1610-0000	Cab and body to have applicable E-ONE logos.	1
CAB DOOR OPTIONS		
1550-0059-000-G6	Reflective Red/Lemon Yellow printed striping positioned in the "A" formation located on the cab door panels.	1
MISC EXTERIOR CAB OPTIONS		
1675-0007	Diesel fuel only label.	1
SEATS		
1685-0012	Seating capacity tag of two occupants.	1
CAB ELECTRICAL OPTIONS		
1750-0308	Battery charging connector 12V Anderson with weatherproof cover. Includes mating connector (ship loose). Location: Driver's door step area.	1
BODY MODEL		
3080-0191	Extruded alum body for Wet-side water tank, single axle chassis with driver side under tank pump. Includes driver and officer side forward lower body compartments, dia plt wheel well area and flat back style rear end with 12" tailboard.	1
BODY SPEC		
3090-0031-T06	The cab to body gap is extended approx 3.0". (Note: this option is to support internal programming functions)	1
DOORS		
3300-0199-003	Door single vertical hinged diamond plate. (For use on products with integral driprail only) Location(S): L1	1
3300-0201-015	Door double vertical hinged w/rotary latches - diamond plate. (For use on products with integral driprail only) Location(S): R1	1
COVERS		
3305-0007-000-13	Vinyl Black hose bed cover with attached rear flap(s).	1
3305-0167-000-13	Vinyl rear cover for diamond plate cover on pre-connect tray. Color: Black	1
PUMP MODULE		
3130-0412	Pump module for use with frame mounted PTO pump. Will be mounted below tank forward of driver side front compartment and will reduce the size of L1 by approximately 39".	1

Salescode	Extended Description	Qty
PUMP PANELS		
3334-0105	Stainless steel driver side pump panel. Wetside tanker with under tank pump only.	1
MISC PUMP PANEL OPTIONS		
4460-0003	Pump panel tags color coded per NFPA compliance.	1
WATER TANK		
4010-0153	Tank 2000 gallon Wetside. Note: Any foam cell(s) in tank will reduce the overall water capacity. Tank capacity is 2000 US gallons / 1665 Imperial gallons / 7571 Liters.	1
WATER TANK OPTIONS		
4020-0004	Newton dump mounting plate.	1
TANK PLUMBING		
4020-0018	Rear tank dump. Includes painted steel assembly with manual actuated valve on top of dump assembly. For use with slip on extension and chute.	1
4450-0010	2" tank fill Akron manual valve.	1
4450-0121	3" Tank to pump Akron air actuated valve w/4" tank connection.	1
4450-0165-199	3" rear direct tank fill. Includes swing handle control, swivel with droop and plug with retainer. Located to officer's side of the rear body.	1
LADDER STORAGE / RACKS		
3340-0408-198	Adjustable ladder brackets. Locate in track driver's side.	1
3340-0409-198	Adjustable tracks (pair). Locate tracks to driver's side assembly. For use with ladder and/or hard suction rack(s).	1
3365-0049	Brand of ladders capable of being carried on unit to be Alco-Lite.	1
3365-0087-C57	The length of ladders capable of being stored shall be the following: 24' 2-section and 14' roof ladder.	1
3365-0189-M13-L13	Manual drop-down portable tank storage rack. Includes forward and rearward securing damp with manual releases. Locate rack to officer side on compartment top of body. Rack sized for steel framed 2100 portable tank.	1
3365-0294	There shall be a metal plate mounted to the side of the portable tank rack to assist in the application of the NFPA stripe and/or Lettering.	1
HANDRAILS / STEPS		
3330-0141-525	Access ladder with aluminum side rails and aluminum ribbed extruded steps for NFPA hosebed access and handrail mounted on upper hosebed side (as applicable). LED lighting provided and positioned to illuminate steps per NFPA.	1

Salescode	Extended Description	Qty
HANDRAILS / STEPS		
	Ladder to be located rear of body officer side.	
MISC BODY OPTIONS		
3090-0002	OAH. Unit has no overall height restrictions.	1
3090-0004	OAL. Unit has no overall length restrictions.	1
3340-0093	Mud flaps, rear, black with E-ONE logo.	1
3340-0523	Hosebed area above booster tank. Includes raised sides and front of water tank, slatted flooring and adjustable divider extrusions.	1
3340-0552	Double pre-connect tray on top of the drivers side compartment top offset to the rear. Tray to be "U" shape to hold 200' of 1.75" DJ (each). Includes hinged diamond plate cover.	1
3340-0588	Slip-on painted steel dump elbow and 36" straight extension chute. Includes body mounted removable support arm and mounting brackets at rear of body for elbow and straight chute.	1
3340-0612	Diamond plate shield over electrical items mounted on extended box at upper rear of Wetside tank.	1
3340-0682	Body mainframe layout line to be 25". Includes body and all applicable modules.	1
3340-1037	Hosebed hoseload allowance on the apparatus shall be 800 lbs.	1
3340-1137-11Z	Equipment allowance on the apparatus shall be 1000 lbs. This allowance is in addition to the weight of the hoses and ground ladders listed in the shop order as applicable.	1
PUMPS		
4005-0103	Rating 500 GPM.	1
4005-0218	Hale AP PTO driven pump. Includes driver side 5" intake with cap. Capacity of 500GPM/1892LPM. Requires primer option. For use with Wetside Tanker only.	1
PUMP CERTIFICATION		
4475-0004	Pump certification 250-500 GPM	1
PUMP OPTIONS		
4015-0073	Manual operated master pump drain. The master drain shall be clearly marked and placed in accessible location below running board on driver side or L1 compartment.	1
4015-0234	Control for engine cooler. Includes Innovative Controls 1/4 turn valve with "T" handle and label. Requires engine cooler option.	1
4015-0241	Trident primer W/2 barrel push button control. For use with up to 1000 GPM pumps.	1

Salescode	Extended Description	Qty
INTAKES		
4440-0005	2.5" Left Intake Akron Manual Valve.	1
INTAKE OPTIONS		
4445-0009	Intake relief valve, Akron.	1
DISCHARGES AND PRECONNECTS		
4415-0014-581	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 1.	1
4415-0014-582	2.5" Left Pump Panel Discharge Akron Manual Valve. Location: left side discharge 2.	1
4415-0875	Pair of 1.5" preconnect discharges with Akron manual valves. For use with narrow Wetside tank with driver side compartment top pre-connect storage. Plumbing to terminate with 1.5" MNST threads.	1
DISCHARGE OPTIONS		
4417-0175	Innovative Controls push/pull valve controls with locking T handles.	1
4417-0176	Innovative Controls 3/4" bleeder/drain valve include lift lever with ergonomic grip.	4
4417-0185	Innovative Controls discharge and intake bezels with integral color code and verbiage for side mount pump panel.	1
PRESSURE GOVERNORS		
4465-0020	Class 1 TRG Plus pressure governor. Includes master intake and discharge gauges, water, oil, volt and tachometer.	1
GAUGES		
4435-0083	Innovative Controls 10 LED SL series water tank level gauge. On pump panel.	1
4435-0246	2.5" Innovative Controls stainless steel case pressure gauge (0-400) with color code bezel.	4
ELECTRICAL SYSTEMS		
5010-0014-G97	Vehicle data recorder for commercial cab - 2009 NFPA compliant. Includes occupant detection with display. Display location: cab dash above transmission shift panel.	1
5010-0036	V-MUX Electrical system for pumper / tanker / rescue.	1
5010-0059-339	VFD Text display for V-MUX electrical system. Location: center of dash.	1
LIGHT BARS		
5300-0267	Light bar Whalen Justice model JE2NFPA 56" LED with clear lenses and MKEZ7	1

Salescode	Extended Description	Qty
LIGHT BARS		
	mounts. N/A on Vista roofs with front facing windows. Includes (4) red corner facing LIN6 LED lights, (6) forward facing CON3 Linear LED lights; (4) red, (2) white. Location: Centered on the front cab roof.	
WARNING LIGHT PACKAGES		
5550-0182-P27	Whelen LED lower level warning light package. Includes (10) red LIN3 lights w/chrome flanges. Locate side facing lights: at forward most position, in rear wheelwell offset to front, and in rear wheelwell offset to rear.	1
WARNING LIGHTS		
5600-0086-479-06	Whelen beacon model RB6T (PR) with Red domes. Location: rear upper body on aerial style brackets.	1
5600-0105-170	Hazard (door ajar) light 2" LED. Location: center overhead.	1
SIRENS		
5500-0015	Whelen model 295SLSA1 siren with microphone (replaced 295HFSA1).	1
5500-0024-170	The electronic siren control is to be located on the center overhead.	1
SPEAKERS		
5510-0029-211	Speaker. Federal Signal Dynamax ES100 with "E-ONE" grille through bumper. Location: officer side front bumper.	1
DOT LIGHTING		
5150-0017	License plate light LED with chrome housing located at the rear of the body.	1
5150-0042	Federal Signal LED tail lights. Includes 4" diameter red LED stop/tail, amber turn and LED clear back-up.	1
5150-0112	Marker light package .75" Dia LED Techniq. Commercial pumper and tanker bodies.	1
LIGHTS - COMPARTMENT, STEP & GROUND		
5380-0200	Ground light package EON LED - small.	1
5380-0205	Cab step lighting package. Includes (2) EON LED lights per side.	1
5380-0255	Compartment light package ROM V4 LED (2) for Wetside tanker. Includes one 12" light per compartment.	1
LIGHTS - DECK AND SCENE		
5390-0076	Hose bed light Truck-Lite LED model 81380. Locate at front of hose bed. Switched with work light switch in cab.	1
5390-0115	Whelen 600 series gradient Super-LED scene lights (6). Switch in cab (driver and	1

Salescode	Extended Description	Qty
LIGHTS - DECK AND SCENE		
	officer side lights switched separately). Lights located (2) each side of body up high (offset forward and rearward) and (2) at rear of body up high. Wet side only.	
LIGHTS - NON-WARNING		
5400-0003	Engine compartment light (EA).	1
5400-0143	Pump panel LED light package for side mount. Includes (3) TracIQ EON lights with S/S housings. Includes S/S light shield. Wet side only.	1
5400-0152	Pump compartment light EON LED. Includes switch on pump operator's panel.	1
MISC ELECTRICAL		
5110-0017	Back-up alarm 97 dB.	1
MISC LOOSE EQUIPMENT		
7900-0014	DOT Required Drive Away Kit - Kit includes three (3) triangular warning reflectors with carrying case. This kit is for the end user and is to remain with the truck.	1
EXTERIOR PAINT		
8100-0377	Body to be unpainted.	1
8100-0400	Wet side water tank to be unpainted.	1
STRIPING		
8300-0002-Q55-12	NFPA Scotchlite Stripe - 4" wide and straight on front/sides of cab and sides/rear of body. Color: White. Location: low on side of cab and low on side of wet side tank.	1
8300-0177-000-72	Chevron "A" style 6" printed sheet Scotchlite striping on rear of Wet side body (on panels only - not tank). Colors to be Yellow/Red.	1
WARRANTY / STANDARD & EXTENDED		
9100-0000	Standard 1 Year Warranty.	1
9100-0004	10 Year/100,000 Mile Structural Warranty for Alum Cab / Body - Statement of Warranty.	1
9100-0005	10 Year Stainless Steel Plumbing Warranty - Statement of Warranty.	1
SUPPORT, DELIVERY, INSPECTIONS AND MANUALS		
9300-0009	Manuals, Operator and Service CD-ROM.	1
9300-0316	Fire Apparatus Safety Guide published by FAMA, latest edition.	1
Dealer Supplied Equipment		