

Global M3 Standard Features :

- Sound Suppressed Cab
- 69 dBA In-Cab Noise Level
- Dust & Weather Sealed Cab with A/C Standard
- Multi-Adjustable Suspension Seat
- Tilt & Telescoping Steering Wheel
- Tinted Safety Windows & Windshield
- Left & Right Dual West Coast Mirrors
- Windshield Wiper/Washer
- Ergonomic Go Pedal
- Coolant Temp, Oil Pressure & Voltmeter Gauges
- Coolant, Eng Oil Pressure & Low Hyd Oil Warning
- Speedometer, Tachometer & Hourmeter
- Fuel Level Gauge
- 230 gal (833L) Polyethylene Water Tank
- 15' (4.6 m) Hydrant Hose with Coupling & Wrench
- Gutter Broom Water Spray Jets (2 Each side)
- Pickup Broom Water Spray Jets (4)
- Low Water Level Light in Cab
- Front Spray Bar
- Buddy Seat
- Dual Front Tires with Front Suspension
- Electric Controls systems Locker
- 5.6 cu yd (4.3 cu meter) Hopper Dump Alarm
- 47" (1194 mm) dia. Gutter Brooms
- In-Cab Gutter Broom Pressure Adjustment
- Tuf-Grip Disposable Gutter Broom Segments
32" x 56.5" Tube Type Pickup Broom
- 58" Wide Squeegee Type Elevator
- Gutter Broom Spotlights
- Sealed Beam Headlights
- Stop/Tail Lights, Clearance Lights
- Two 18 gal (68 L) Hydraulic Oil Tanks
- Hydraulic Manifolds in LH Fender
- 12.5' Turning Radius with Front Suspension
- 120 amp Heavy-Duty Alternator
- All Sheet Metal Surfaces Primer Powder Coated
- Sheet Metal Surfaces Powder Coated
- Fender Mounted Tool Box
- Integral Cab Limb Guard Protection
- Front & Rear Tie Downs with Tow Hooks
- IN CAB Controlled LEAF GATE STANDARD
- STANDARD ERGO SWITCH (One Button Operation)
- REAR VIEW CAMERA WITH 7" LCD DISPLAY
- John Deere 4045 TF Tier 3/IT4 Engine



ISO 9001:2008



5405 Industrial Parkway
San Bernardino, CA 92407 USA
Phone: 909-713-1600
info@globalsweeper.com
www.GlobalSweeper.com

