

**SUGGESTIONS FOR WRITING BID SPECIFICATIONS ON THE
ADVANCE *All Cleaner*[™] XP**

| | |
|-----------------------------|--|
| GENERAL | The machine shall be multi-functional with the ability to be used as a pressure washer, chemical applicator, wet/dry vacuum, blower, and carpet extractor. Unit shall be able to store all standard tools onboard. |
| VACUUM MOTOR | Shall be 2-stage, 900 Watts with a by-pass design. Shall be capable of producing 81 inch sealed waterlift and airflow shall be 97 cfm (2,747 L/min.). Motor shall be protected by a float shut-off system and an in-line strainer. |
| SOLUTION FEED SYSTEM | Shall use a 500 psi rated pump which dispenses solution through a 15 foot (4.6 m) hose at 0.75 g.p.m. Shall be able to draw chemical through one of two chemical feed lines. |
| SOLUTION TANK | Shall be a minimum capacity of 20 gallons (76 L) and constructed of rotational molded polyethylene. Shall have a drain to allow full discharge of all solution. Shall have an attached fill hose. |
| RECOVERY TANK | Shall be 12 gallon (45 L) actual wet recoverable capacity constructed of rotational molded polyethylene. Shall be sloped to drain 100% into a commode or slop sink with a 1.25 inch (3.18 cm) diameter by 24 inch (61 cm) long drain hose. Shall be able to connect to a 15 foot (4.6 m) long, 1.5 inch (3.8 cm) diameter recovery hose. Shall be able to connect to an optional front mount squeegee with a lever on the rear of the machine for raising and lowering the squeegee. |
| MOTOR / PUMP HOUSING | Shall be constructed of rotational-molded polyethylene and removable without tools allowing the entire electrical system to be serviced outside the machine. |
| CHEMICAL SYSTEM | Shall be able to accommodate 2 gallon containers of all shapes. Shall have a front mounted switch that toggles between each chemical container and plain water. |
| BLOWER | Shall use an optional 13 foot (4 m) hose, connected to the exhaust air nozzle. |
| POWER CABLE | Shall be no less than 25 foot (7 m), detachable, GFCI, safety yellow in color, 16/3 conductor, non-marking, yellow, vinyl covered, water-resistant material. |
| WHEELS | Shall have two 4 inch (10 cm) front swivel casters and two 10 inch (25 cm) by 1.75 inch (4 cm) rear wheels. |
| HANDLE | Shall have an ergonomic transport handle with a clip to store a mop handle. |
| TOOLS/ ACCESSORIES | Shall have as standard equipment a two piece two-bend self locking aluminum wand, variable pressure gun, 52 inch (132 cm) mop handle, 14 inch (35.5 cm) squeegee floor tool, scrub brush with squeegee, 12 inch hand squeegee tool, 7 pc metering tip packet and a priming hose. Shall have a wet floor sign holder. |
| DIMENSIONS | Shall be no more than: Height – 38.5 inches (98 cm) Width – 20 inches (51 cm) Length – 34 inches (86 cm) |
| WEIGHT | Shall be no more than: Net – 92 pounds (42 kg) |

THE MACHINE SHALL BE AN ADVANCE *All Cleaner*[™] XP