



2023

JCB
Hydraulic Excavators



**JCB, Inc. North American
Machine Price List
In U.S. Dollars
Effective: Jan 01, 2023**

Changes to specifications and/or prices may occur.
Please refer to the product manager for updates.



2023

JCB Hydraulic Excavator I3IX



JCB, Inc. North American Machine Price List In U.S. Dollars Effective: Jan 01, 2023

Changes to specifications and/or prices may occur.
Please refer to the product manager for updates.



U.S. Dollar Price Page

131X Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

STANDARD EQUIPMENT

ENGINE	JCB Ecomax 444, 74 HP at 2,200 RPM. Four stroke, four-cylinder in-line, common rail, direct injection, turbo charged and intercooled diesel engine. Low emission engine, EPA Tier 4 Final compliant. Dry element with secondary safety element and in cab warning indicator.
HYDRAULICS	Variable flow load sensing system with on demand and servo operated multi-function open center control. Independent servo gear pump. Two main axial piston pumps yield combined flow of 68.6 GPM. Servo pump flow: 7.9 GPM.
OPERATORS AREA	Air conditioned cab, noise and vibration isolated by six hydraulically damped resilient mountings. Opening door window. Fan forced fresh air ventilation with defogger and washer/wiper. Fully adjustable suspension seat with seatbelt, headrest, armrests, and backrest recline. Two boom and one mainframe work light
CONTROLS	Excavator controls are ISO pattern, servo operated, with in cab 7" digital display and change over control to SAE found in fuse box. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance and a console mounted switch.
UPPER	Monoboomb with choice of dipper arms to suit dig depth requirements. No reinforcing required for hammer operations. Boom: 15' 5" (4.7m). Dippers: 8' 2" (2.5m), 9' 10" (3.0m).
UNDERCARRIAGE	The undercarriage gives excellent stability, is a fully welded X-frame type with undercarriage center cover, engine undercover and travel drive motor, cover and shields. Twin top and seven bottom rollers are heat-treated, sealed and lubricated. Track idler is sealed and lubricated and incorporates spring cushion recoil.
TRACK DRIVE	Full hydrostatic, 2 speed, driven by two axial piston motors. Motors are guarded in undercarriage frame for protection from debris. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 4.1 MPH, low speed is 2.4 MPH. Parking brake is disc type, spring applied, hydraulic release.
ELECTRICAL	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 100 amp output alternator with 12 volt in-cab supply.
LIVELINK	5 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
OPERATING WEIGHT	Equipped with standard boom, dipper, 24" track shoes and excavator bucket: apprx. 30,350 lbs.
WARRANTY	3 Year/3,000 hour full coverage warranty (please see the machine warranty certificate for details).



I3IX Hydraulic Excavator



U.S. Dollar Price Page

Effective: Jan 01, 2023

F.O.B. Savannah, GA

SECTION I - YELLOW SERIES

Select one of the following machine Package Build(s).

If none of the Package Build combinations meet your requirements, please order a machine using the Custom Build Sections following.

SALES CODE	ITEM	LIST PRICE
9508	I3IX LC T4F Monoboom	\$154,247
900A030	Long Undercarriage 1990mm (78in) Gauge, 3590mm (141in) Long	\$0
900B521	24" (600MM), Triple Grouser - 44 Link Tracks	\$3,984
900CD00	Monoboom, 0 HBCV, 3.0m Dipper	\$1,459
900D511	Tipping Link: Max Capacity Lifting Shackle	\$713
900E703	US Homologation PTO Engine 74HP	\$0
900KT47	Thumb Ready 3.0m Dipper with High Flow Advanced Tool Select	\$4,520
900MA14	Quickhitch Arm & Boom Mono 3.0m Dipper	\$2,172
900RB01	Radio - Bluetooth Compatible	\$233
900RB02	Deluxe Seat - Air Suspension and Heated Base	\$1,006

LIST PRICE **\$168,334**



U.S. Dollar Price Page

I3IX Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each category below. Select Options and Attachments from Sections 3 and 4 as needed.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	PRIMARY BUILD	LIST PRICE
9508	I3IX LC T4F Monoboom	\$154,247
UNDERCARRIAGE		
900A030	Long Undercarriage 1990mm (78in) Gauge, 3590mm (141in) Long	\$0
TRACK PADS		
900B521	24" (600MM), Triple Grouser - 44 Link Tracks	\$3,984
MONO BOOM AND DIPPER (includes brackets for all attachment pipework)		
900CD00	Monoboom, 0 HBCV, 3.0m Dipper	\$1,459
TIPPING LINK		
900D511	Tipping Link: Max Capacity Lifting Shackle	\$713
LANGUAGE PACK		
900E703	US Homologation PTO Engine 74HP	\$0



U.S. Dollar Price Page

I3IX Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION 3 - OPTIONS - NEW CUSTOM FACTORY BUILT ORDERS

Select Optional Equipment as desired, within limitations if indicated.

SALES CODE	HYDRAULIC ATTACHMENT PIPEWORK	LIST PRICE
900KT47	Thumb Ready 3.0m Dipper with High Flow Advanced Tool Select	\$4,520
Notes	<ul style="list-style-type: none">• High flow circuit pipework is dual function. The merged circuit adds in up to 70% of the flow from the second main pump. When operator selects hammer function hydraulic flow is delivered in one direction to run hammer. Circuit is operated by foot pedal. When auxiliary function is selected the same pump flow is delivered bi-directionally to run tool. Circuit can be operated by the foot pedal, hand control buttons or slider depending on code available.• Low flow circuit: separate pipework set delivers servo pump flow bi-directionally to run tool. Operated by hand control buttons or slider.• For additional factory installed hydraulic pipework options call JCB Product Marketing.• Shut-off ball valve for hammer and auxiliary pipework available through JCB Parts Dept.	
OPTIONS		
900RB01	Radio - Bluetooth Compatible	\$233
900RB02	Deluxe Seat - Air Suspension and Heated Base	\$1,006



U.S. Dollar Price Page

I3IX Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS

Select Attachments as desired, within limitations if indicated.

SALES CODE	EXCAVATOR BUCKETS	LIST PRICE
YWSEA01	Add 328/00500. 36" Bucket	\$5,438
YWSEA02	Add 980/A8250. Hydraulic Coupler	\$8,061
YWSEA03	Add 980/B0201. Hm090T	\$25,451
YWSEA04	Add 328/00498. 24" Bucket	\$4,827



2023

**JCB Hydraulic Excavator
JZ141D**



**JCB, Inc. North American
Machine Price List
in U.S. Dollars
Effective: Jan 01, 2023**

Changes to specifications and/or prices may occur.
Please refer to the product manager for updates.



U.S. Dollar Price Page

JZ141D

Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

STANDARD EQUIPMENT

ENGINE	JCB Ecomax 444, 74 HP at 1,800 RPM. Four-cylinder water cooled common rail direct injection diesel engine. Low emission engine, EPA Tier 4 Final compliant. Dual element air cleaner.
HYDRAULICS	Variable flow load sensing system with on demand and servo operated multi-function open center control. independent servo gear pump. Two main axial piston pumps yield combined flow of 68.6 GPM. Servo pump flow: 5.3 GPM.
OPERATORS AREA	Air conditioned cab, noise and vibration isolated by six hydraulically damped resilient mountings. Opening door window. Fan forced fresh air ventilation with defogger and washer/wiper. Fully adjustable suspension seat with seatbelt, headrest, armrests, and backrest recline. Two boom and one mainframe work light
CONTROLS	Excavator controls are ISO pattern, servo operated, with in cab 7" digital display and change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance and a console mounted switch.
UPPER	Monoboom with choice of dipper arms to suit dig depth requirements. No reinforcing required for hammer operations. Boom: 15' 5" (4.7m). Dippers: 8' 2" (2.5m), 9' 10" (3.0m).
UNDERCARRIAGE	The undercarriage gives excellent stability, is a fully welded X-frame type with undercarriage center cover, engine undercover and travel drive motor, cover and shields. Twin top and seven bottom rollers are heat-treated, sealed and lubricated. Track idler is sealed and lubricated and incorporates spring cushion recoil.
TRACK DRIVE	Full hydrostatic, 2 speed, driven by two axial piston motors. Motors are guarded in undercarriage frame for protection from debris. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 4.1 MPH, low speed is 2.4 MPH. Parking brake is disc type, spring applied, hydraulic release.
ELECTRICAL	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 55 amp output alternator with 12 volt in-cab supply.
LIVELINK	5 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
OPERATING WEIGHT	Equipped with standard boom, dipper, 24" track shoes and excavator bucket: apprx. 35,280 lbs.
WARRANTY	3 Year/3,000 hour full coverage warranty (please see the machine warranty certificate for details).



U.S. Dollar Price Page

JZ141D

Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION I - YELLOW SERIES

Select one of the following machine Package Build(s).

If none of the Package Build combinations meet your requirements, please order a machine using the Custom Build Sections following.

SALES CODE	ITEM	LIST PRICE
9145	JZ141 LC T4F MONOBOOM WITH DOZER	\$191,706
900A483	Long Undercarriage, 1990MM (78in) Gauge, 3585MM (141in) Long	\$0
900B614	600MM (24in), 44 Links, Triple Grouser - Dozer Width 2610MM (103in)	\$3,983
900C393	Monoboom, 0 HBCV, 3.0M Dipper	\$1,412
900D511	Tipping Link: Max Capacity Lifting Shackle	\$713
900EC07	USA Homologation Pack	\$0
900KM24	Hammer/Aux Prop. Controls - 3.0M Dipper	\$2,043
900M036	Hydraulic Quick Hitch Lite installation	\$2,102
900R001	AM/FM Radio	\$227
900R011	Deluxe Seat - Air Suspension And Heated Base	\$974

LIST PRICE **\$203,160**



U.S. Dollar Price Page

JZ141D

Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each category below. Select Options and Attachments from Sections 3 and 4 as needed.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	PRIMARY BUILD	LIST PRICE
9145	JZ141 LC T4F MONOBOOM WITH DOZER	\$191,706
UNDERCARRIAGE		
900A483	Long Undercarriage, 1990MM (78in) Gauge, 3585MM (141in) Long	\$0
TRACK PADS		
900B614	600MM (24in), 44 Links, Triple Grouser - Dozer Width 2610MM (103in)	\$3,983
900B615	700MM (28IN), 44 LINKS, Triple Grouser - Dozer Width 2710 MM(107IN)	\$4,923
MONO BOOM AND DIPPER (includes brackets for all attachment pipework)		
900C393	Monoboom, 0 HBCV, 3.0M Dipper	\$1,412
TIPPING LINK		
900D395	Tipping Link No Lift Shackle	\$0
900D511	Tipping Link: Max Capacity Lifting Shackle	\$713
LANGUAGE PACK		
900EC07	USA Homologation Pack	\$0



JZ141

Hydraulic Excavator



U.S. Dollar Price Page

Effective: Jan 01, 2023

F.O.B. Savannah, GA

SECTION 3 - OPTIONS - NEW CUSTOM FACTORY BUILT ORDERS

Select Optional Equipment as desired, within limitations if indicated.

SALES CODE	HYDRAULIC ATTACHMENT PIPEWORK	LIST PRICE
900KM23	Hammer/Aux Prop. Controls - 2.5M Dipper	\$2,043
900KM24	Hammer/Aux Prop. Controls - 3.0M Dipper	\$2,043
Notes	<ul style="list-style-type: none">• High flow circuit pipework is dual function. The merged circuit adds in up to 70% of the flow from the second main pump. When operator selects hammer function hydraulic flow is delivered in one direction to run hammer. Circuit is operated by foot pedal. When auxiliary function is selected the same pump flow is delivered bi-directionally to run tool. Circuit can be operated by the foot pedal, hand control buttons or slider depending on code available.• Low flow circuit: separate pipework set delivers servo pump flow bi-directionally to run tool. Operated by hand control buttons or slider.• For additional factory installed hydraulic pipework options call JCB Product Marketing.• Shut-off ball valve for hammer and auxiliary pipework available through JCB Parts Dept.	
OPTIONS		
900M036	Hydraulic Quick Hitch Lite installation	\$2,102
900P033	Scavenge Type Precleaner System	\$361
900R001	AM/FM Radio	\$227
900R035	Rainguard - Cab Mounted	\$649
900R130	Lower Level Windscreen Wiper	\$342
900S010	Vandal Cover Kit	\$3,061
900S020	FOPS Level 2 Guard - Front Windshield And Roof	\$7,535
900S025	Mesh Screen Guard For Front Windshield	\$1,981
900S039	LED Worklights Standard 2 Boom, 1 CWT, 2 Toolbox	\$1,091
900S130	Additional Worklights	\$630
900S140	Amber Beacon - Cab Roof	\$245
900X531	Twin Track Guides	\$1,883



U.S. Dollar Price Page

JZ14I

Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION 3 - OPTIONS - NEW CUSTOM FACTORY BUILT ORDERS CONT.

OPTIONS CONT.



U.S. Dollar Price Page

JZ141D

Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS

Select Attachments as desired, within limitations if indicated.

SALES CODE	EXCAVATOR BUCKETS	LIST PRICE
YWSEA01	Add 328/00500. 36" Bucket	\$5,438
YWSEA02	Add 980/A8250. Hydraulic Coupler	\$8,061
YWSEA03	Add 980/B0201. Hm090T	\$25,451
YWSEA04	Add 328/00498. 24" Bucket	\$4,827



2023

JCB Hydraulic Excavator I50X



JCB, Inc. North American Machine Price List in U.S. Dollars Effective: Jan 01, 2023

Changes to specifications and/or prices may occur.
Please refer to the product manager for updates.



U.S. Dollar Price Page

I50X

Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

STANDARD EQUIPMENT

ENGINE	JCB Ecomax 444, 109 HP at 2,200 RPM. Four-cylinder water cooled common rail direct injection diesel engine. Low emission engine, EPA 4 Final compliant. Dual element air cleaner.
HYDRAULICS	Variable flow load sensing system with on demand and servo operated multi-function open center control. independent servo gear pump. Two main axial piston pumps yield combined flow of 68 GPM. Servo pump flow: 7.9 GPM.
OPERATORS AREA	Air conditioned cab, noise and vibration isolated by six hydraulically resilient mountings. Opening door window. Fan forced fresh air with defogger and washer/wiper. Fully adjustable suspension seat with seatbelt, headrest, armrests, and backrest recline. Two boom and one mainframe work light.
CONTROLS	Excavator controls are ISO pattern, servo operated, within electrical fuse box change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance.
UPPER	Monoboom with choice of dipper arms to suit dig depth requirements. No reinforcing required for hammer operations. Boom: 16' 11" (5.15m). Dippers: 8' 10" (2.7m), 10' 10" (3.05m).
UNDERCARRIAGE	The long undercarriage gives excellent stability, is a fully welded X-frame type with undercarriage center cover, engine undercover and travel drive motor, cover and shields. Twin top and seven bottom rollers are heat-treated, sealed and lubricated. Track idler is sealed and lubricated and incorporates spring cushion recoil.
TRACK DRIVE	Full hydrostatic, 2 speed, driven by two axial piston motors. Motors are guarded in undercarriage frame for protection from debris. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 4.1 MPH, low speed is 2.4 MPH. Parking brake is disc type, spring applied, hydraulic release.
ELECTRICAL	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 100 amp output alternator with 12 volt in-cab supply.
LIVELINK	5 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
OPERATING WEIGHT	Equipped with standard boom, dipper, 24" track shoes and excavator bucket: apprx. 39,916 lbs.
WARRANTY	3 Year/3,000 hour full coverage warranty (please see the machine warranty certificate for details).



U.S. Dollar Price Page

I50X Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION I - YELLOW SERIES

Select one of the following machine Package Build(s).

If none of the Package Build combinations meet your requirements, please order a machine using the Custom Build Sections following.

SALES CODE	ITEM	LIST PRICE
9510	I50X LC T4F Monoboom	\$159,737
900A030	Long Undercarriage 1990mm (78in) Gauge, 3590mm (141in) Long	\$0
900B521	24" (600MM), Triple Grouser - 44 Link Tracks	\$3,984
900CD00	Monoboom, 0 HBCV, 3.0m Dipper	\$1,459
900D511	Tipping Link: Max Capacity Lifting Shackle	\$713
900E702	US HOMOLOGATION PTO ENGINE 108HP	\$0
900KT47	Thumb Ready 3.0m Dipper with High Flow Advanced Tool Select	\$4,520
900MA14	Quickhitch Arm & Boom Mono 3.0m Dipper	\$2,172
900RB01	Radio - Bluetooth Compatible	\$233
900RB02	Deluxe Seat - Air Suspension and Heated Base	\$1,006

LIST PRICE \$173,823



U.S. Dollar Price Page

I50X Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each category below. Select Options and Attachments from Sections 3 and 4 as needed.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	PRIMARY BUILD	LIST PRICE
9510	I50X LC T4F Monoboom	\$159,737
9511	I50X LC Dozer T4F Monoboom	\$175,686
UNDERCARRIAGE FOR PRIMARY BUILD 9474		
900A030	Long Undercarriage 1990mm (78in) Gauge, 3590mm (141in) Long	\$0
TRACK PADS		
900B521	24" (600MM), Triple Grouser - 44 Link Tracks	\$3,984
MONO BOOM AND DIPPER (includes brackets for all attachment pipework)		
900CD00	Monoboom, 0 HBCV, 3.0m Dipper	\$1,459
TIPPING LINK		
900D511	Tipping Link: Max Capacity Lifting Shackle	\$713
LANGUAGE PACK		
900E702	US HOMOLOGATION PTO ENGINE 108HP	\$0



U.S. Dollar Price Page

I50X

Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION 3 - OPTIONS - NEW CUSTOM FACTORY BUILT ORDERS

Select Optional Equipment as desired, within limitations if indicated.

SALES CODE	HYDRAULIC ATTACHMENT PIPEWORK	LIST PRICE
900KT47	Thumb Ready 3.0m Dipper with High Flow Advanced Tool Select	\$4,520
Notes	<ul style="list-style-type: none">• High flow circuit pipework is dual function. The merged circuit adds in up to 70% of the flow from the second main pump. When operator selects hammer function hydraulic flow is delivered in one direction to run hammer. Circuit is operated by foot pedal. When auxiliary function is selected the same pump flow is delivered bi-directionally to run tool. Circuit can be operated by the foot pedal, hand control buttons or slider depending on code available.• Low flow circuit: separate pipework set delivers servo pump flow bi-directionally to run tool. Operated by hand control buttons or slider.• For additional factory installed hydraulic pipework options call JCB Product Marketing.• Shut-off ball valve for hammer and auxiliary pipework available through JCB Parts Dept.	
OPTIONS		
900MA14	Quickhitch Arm & Boom Mono 3.0m Dipper	\$2,172
900RB01	Radio - Bluetooth Compatible	\$233
900RB02	Deluxe Seat - Air Suspension and Heated Base	\$1,006



U.S. Dollar Price Page

I50X

Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS

Select Attachments as desired, within limitations if indicated.

SALES CODE	EXCAVATOR BUCKETS	LIST PRICE
YWSEA01	Add 328/00500. 36" Bucket	\$5,438
YWSEA02	Add 980/A8250. Hydraulic Coupler	\$8,061
YWSEA03	Add 980/B0201. Hm090T	\$25,451
YWSEA04	Add 328/00498. 24" Bucket	\$4,827



2023

**JCB Hydraulic Excavator
JSI 60LC, JSI 60NLC**



**JCB, Inc. North American
Machine Price List
in U.S. Dollars
Effective: Jan 01, 2023**

Changes to specifications and/or prices may occur.
Please refer to the product manager for updates.



U.S. Dollar Price Page

JSI60 Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

STANDARD EQUIPMENT

ENGINE	JCB Ecomax 444, 125 net HP at 2,200 RPM, Tier 4 Final. Water cooled 4 Cycle, 4 Cylinder, in-line, common rail, direct injection, variable turbocharged, intercooled diesel. Low emission engine designed to with US EPA standards. Combines single face radiator and hydraulic oil cooler. Selective catalytic reduction (SCR) system.
HYDRAULICS	Variable flow load sensing system with on demand and servo operated multi-function open center control. independent servo gear pump. Two main axial piston pumps yield combined flow of 86 GPM. Servo pump flow: 5.5 GPM.
OPERATORS AREA	Climate controlled, noise and vibration isolated by six hydraulically damped resilient mountings. Full opening door window. Fan forced fresh ventilation with defogger and washer/wiper. Fully adjustable, high back suspension seat with seatbelt, headrest, armrests, and backrest recline. Two boom and one mainframe work light.
CONTROLS	Excavator controls are ISO pattern, servo operated, with in cab 7.0" digital display and change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance and a console mounted switch. Rearview camera standard.
UPPER	Monoboomb with choice of dipper arms to suit dig depth requirements. No reinforcing required for hammer operations. Boom: 16' 11" (5.15m). Dippers: 8' 10" (2.7m), 10' 10" (3.05m).
UNDERCARRIAGE	The long undercarriage gives excellent stability, is a fully welded X-frame type with undercarriage center cover, engine undercover and travel drive motor, cover and shields. Twin top and seven bottom rollers are heat-treated, sealed and lubricated. Track idler is sealed and lubricated and incorporates spring cushion recoil.
TRACK DRIVE	Full hydrostatic, 2 speed, driven by two axial piston motors. Motors are guarded in undercarriage frame for protection from debris. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 3.4 MPH, low speed is 2.0 MPH. Parking brake is disc type, spring applied, hydraulic release.
ELECTRICAL	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 55 amp output alternator with 12 volt in-cab supply.
LIVELINK	5 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
OPERATING WEIGHT	Equipped with standard boom, dipper, 24" track shoes and excavator bucket: appr. 38,500 lbs.
WARRANTY	3 Year/3,000 hour full coverage warranty (please see the machine warranty certificate for details).



U.S. Dollar Price Page

JSI60

Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION I - YELLOW SERIES

Select one of the following machine Package Build(s).

If none of the Package Build combinations meet your requirements, please order a machine using the Custom Build Sections following.

SALES CODE	ITEM	LIST PRICE
9531	JSI60 NLC Primary Build Tier 4 Final	\$191,611
900A427	Narrow Long Undercarriage, 78" (1990MM) Gauge, 155" (3940MM) Long	\$0
900B574	24" (600MM), Triple Grouser - 43 Link Chain	\$4,021
900C121	Monoboom With 10' 0" (3.05 M) Dipper	\$1,425
900D403	Tipping Link With Lifting Shackle	\$636
900E2E6	North American Manual Pack	\$0
900KD09	Hammer/Aux Prop. Controls - 3.05M Dipper	\$2,042
900M038	Quick Hitch Lite installation Kit	\$2,102
900R001	AM/FM Radio	\$227
900X387	Shut-Off Valves For Auxiliary/Hammer Circuit (For 10' 0" (3.05M) Dipper)	\$970
LIST PRICE		\$203,033



JSI60

Hydraulic Excavator



U.S. Dollar Price Page

Effective: Jan 01, 2023

F.O.B. Savannah, GA

SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each category below. Select Options and Attachments from Sections 3 and 4 as needed.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	PRIMARY BUILD	LIST PRICE
9530	JSI60 LC Primary Build Tier 4 Final	\$191,611
9531	JSI60 NLC Primary Build Tier 4 Final	\$191,611
UNDERCARRIAGE FOR PRIMARY BUILD 9530		
900A425	Long Undercarriage, 87" (2200MM) Gauge, 155" (3940MM) Long	\$0
UNDERCARRIAGE FOR PRIMARY BUILD 9531		
900A427	Narrow Long Undercarriage, 78" (1990MM) Gauge, 155" (3940MM) Long	\$0
TRACK PADS		
900B574	24" (600MM), Triple Grouser - 43 Link Chain	\$4,021
900B575	28" (700MM), Triple Grouser- 43 Link Chain	\$4,966
MONO BOOM AND DIPPER (includes brackets for all attachment pipework)		
900C120	Monoboom With 8' 10" (2.7 M) Dipper	\$1,425
900C121	Monoboom With 10' 0" (3.05 M) Dipper	\$1,425
TIPPING LINK		
900D403	Tipping Link With Lifting Shackle	\$636
LANGUAGE PACK		
900E2E6	North American Manual Pack	\$0



JSI60

Hydraulic Excavator



U.S. Dollar Price Page

Effective: Jan 01, 2023

F.O.B. Savannah, GA

SECTION 3 - OPTIONS - NEW CUSTOM FACTORY BUILT ORDERS

Select Optional Equipment as desired, within limitations if indicated.

SALES CODE	HYDRAULIC ATTACHMENT PIPEWORK	LIST PRICE
900KD08	Hammer/Aux Prop. Controls - 2.7M Dipper	\$2,042
900KD09	Hammer/Aux Prop. Controls - 3.05M Dipper	\$2,042
Notes	<ul style="list-style-type: none"> • High flow circuit pipework is dual function. The merged circuit adds in up to 70% of the flow from the second main pump. When operator selects hammer function hydraulic flow is delivered in one direction to run hammer. Circuit is operated by foot pedal. When auxiliary function is selected the same pump flow is delivered bi-directionally to run tool. Circuit can be operated by the foot pedal, hand control buttons or slider depending on code available. • Low flow circuit: separate pipework set delivers servo pump flow bi-directionally to run tool. Operated by hand control buttons or slider. • For additional factory installed hydraulic pipework options call JCB Product Marketing. • Shut-off ball valve for hammer and auxiliary pipework available through JCB Parts Dept. 	
	OPTIONS	
	900M038 Quick Hitch Lite installation Kit	\$2,102
	900R001 AM/FM Radio	\$227
	900R011 Deluxe Seat - Air Suspension And Heated Base	\$974
	900R035 Rainguard - Cab Mounted	\$649
	900R130 Lower Level Windscreen Wiper	\$342
	900S010 Vandal Cover Kit	\$3,061
	900S020 FOPS Level 2 Guard - Front Windshield And Roof	\$7,535
	900S025 Mesh Screen Guard For Front Windshield	\$1,981
	900S034 LED Worklights	\$1,092
	900S130 Additional Worklights	\$630
	900S140 Amber Beacon - Cab Roof	\$245
	900S210 Top Around Handrail	\$1,892
	900V005 HP32 Hydraulic Oil - For Cold Climate Operation	\$0
	900V006 HP68 Hydraulic Oil - For Hot Climate Operation	\$0
	900X076 Refueling Pump	\$791
	900X386 Shut-Off Valves For Auxiliary/Hammer Circuit (For 8' 10" (2.7M) Dipper)	\$970
	900X387 Shut-Off Valves For Auxiliary/Hammer Circuit (For 10' 0" (3.05M) Dipper)	\$970
	900X532 Twin Track Guides For Heavy Duty Machine	\$941



U.S. Dollar Price Page

JSI60

Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS

Select Attachments as desired, within limitations if indicated.

SALES CODE	EXCAVATOR BUCKETS	LIST PRICE
YWSEA05	Add 328/00513. 42" Bucket	\$6,977
YWSEA06	Add 980/A8251. Hydraulic Coupler	\$9,206
YWSEA07	Add 980/B0204. Hm120T	\$30,417



2023

JCB Hydraulic Excavator 220X



JCB, Inc. North American Machine Price List in U.S. Dollars Effective: Jan 01, 2023

Changes to specifications and/or prices may occur.
Please refer to the product manager for updates.



U.S. Dollar Price Page

220X

Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

STANDARD EQUIPMENT

ENGINE	JCB Ecomax 448, 173 Net HP at 2000 RPM, Tier 4 Final. 4-cycle, 4-cylinder in line, common rail, direct injection, variable geometry turbocharged, intercooled diesel. Low emission engine designed to with US EPA emission standard. Dual element air cleaner. Combined single face radiator and hydraulic oil cooler. Selective Catalytic Reduction (SCR) System.
HYDRAULICS	Variable flow load sensing system with on demand and servo operated multi-function open center control. independent servo gear pump. Two main axial piston pumps yield combined flow of 120 GPM. Servo pump flow: 4.2 GPM.
OPERATORS AREA	JCB Command Plus Cab. Climate controlled, noise and vibration isolated by four hydraulically damped resilient mountings. Full opening front window. Fan forced fresh air ventilation with defogger and washer/wiper. Fully adjustable, high back air suspension seat with seatbelt, headrest, armrests and backrest recline. Two boom and two mainframe work light.
CONTROLS	Excavator controls are ISO pattern, servo operated, with in cab 7.0" digital display and change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance and a console mounted switch. Rearview camera standard.
UPPER	Monoboam with choice of dipper arms to suit dig depth requirements. No reinforcing required for hammer operations. Boom: 18' 8" (5.70m). Dippers: 7' 10" (2.40m), 9' 10" (3.0m).
UNDERCARRIAGE	The long undercarriage gives excellent stability, is a fully welded X-frame type with flush fitted, heavy duty swing turret cover and heavy duty undercover. Two top and eight bottom rollers are sealed and Track idler is sealed and lubricated and incorporates spring cushion recoil.
TRACK DRIVE	Full hydrostatic, 2 speed, driven by two axial piston motors. Flush fitted heavy duty track motor guards. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 3.5 MPH, low speed is 2.0 MPH. Parking brake is disc type, spring applied, hydraulic release.
ELECTRICAL	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 100 amp output alternator with 12 volt in-cab supply.
LIVELINK	5 year subscription allows for enhanced machine security, improved service monitoring, and modernized fleet control.
OPERATING WEIGHT	Equipped with standard boom, dipper, 32" track shoes and excavator bucket: apprx. 52,450 lbs.
WARRANTY	3 Year/3,000 hour full coverage warranty (please see the machine warranty certificate for details).



U.S. Dollar Price Page

220X Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION I - YELLOW SERIES

Select one of the following machine Package Build(s).

If none of the Package Build combinations meet your requirements, please order a machine using the Custom Build Sections following.

SALES CODE	ITEM	LIST PRICE
9282	220X LC Mono T4F	\$196,552
900AB01	Long Carriage 2390MM (94in) Gauge 4460MM (176in) Long	\$0
900BA07	800MM (31in) Track Plates, Triple Grouser, 49Links,Step Extensions	\$11,233
900CC01	Monoboom,0 HBCV, 3.0M Dipper	\$2,502
900DC11	Tipping Link- 17 Tonne Lug Tipping Link Only	\$671
900ED02	US Language Pack	\$0
900KR77	Thumb Ready 3.0m Dipper HF ATS	\$5,259
900MA02	Hydraulic Quick Hitch installation For 3.0M Mono Dipper	\$2,177
900RB01	Radio - Bluetooth Compatible	\$233
900RB02	Deluxe Seat - Air Suspension and Heated Base	\$1,006
LIST PRICE		\$219,633



U.S. Dollar Price Page

220X

Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each category below. Select Options and Attachments from Sections 3 and 4 as needed.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	PRIMARY BUILD	LIST PRICE
9282	220X LC Mono T4F	\$196,552
9286	220X LCD Mono T4F	\$212,543
UNDERCARRIAGE FOR PRIMARY BUILD 9475		
900AB01	Long Carriage 2390MM (94in) Gauge 4460MM (176in) Long	\$0
900AB04	Long Carriage 2390MM (94in) Gauge 4460MM (176in) Long - Dozer included	\$0
TRACK PADS FOR PRIMARY BUILD 9475		
900BA07	800MM (31in) Track Plates, Triple Grouser, 49Links, Step Extensions	\$11,233
900BA16	600MM Dozer Blade Tracks	\$5,239
900BA17	700MM Dozer Blade Tracks	\$7,484
MONO BOOM AND DIPPER (includes brackets for all attachment pipework)		
900CC01	Monoboom, 0 HBCV, 3.0M Dipper	\$2,502
TIPPING LINK		
900DC11	Tipping Link- 17 Tonne Lug Tipping Link Only	\$671
LANGUAGE PACK		
900ED02	US Language Pack	\$0



U.S. Dollar Price Page

220X Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION 3 - OPTIONS - NEW CUSTOM FACTORY BUILT ORDERS

Select Optional Equipment as desired, within limitations if indicated.

SALES CODE	HYDRAULIC ATTACHMENT PIPEWORK	LIST PRICE
900KR14	Hammer/Aux/Merged Prop.Controls - 3.0M Dipper	\$3,947
900KR77	Thumb Ready 3.0m Dipper HF ATS	\$5,259
QUICKHITCH OPTIONS		
900MA02	Hydraulic Quick Hitch installation For 3.0M Mono Dipper	\$2,177
CAB OPTIONS		
900RB01	Radio - Bluetooth Compatible	\$233
900RB02	Deluxe Seat - Air Suspension and Heated Base	\$1,006



U.S. Dollar Price Page

220X

Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION 3 - OPTIONS - NEW CUSTOM FACTORY BUILT ORDERS CONT.

SAFETY OPTIONS

OPTION PACKS

HYDRAULIC OIL OPTIONS

MISCELLANEOUS



U.S. Dollar Price Page

220X Hydraulic Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS

Select Attachments as desired, within limitations if indicated.

SALES CODE	EXCAVATOR BUCKETS	LIST PRICE
YWSEA08	Add 328/00529. 48" Bucket	\$8,722
YWSEA09	Add 980/A8252. Hydraulic Coupler	\$10,340
YWSEA10	Add 980/B0210. Hm180T	\$37,973



2023

**JCB Compact Excavator
245XR**



**JCB, Inc. North American
Machine Price List
In U.S. Dollars
Effective: Jan 01, 2023**

Changes to specifications and/or prices may occur.
Please refer to the product manager for updates



U.S. Dollar Price Page

245XR

Large Excavator

Effective: Jan 01, 2023



F.O.B. Savannah, GA

STANDARD EQUIPMENT

ENGINE	JCB Ecomax 448, 173 Net HP at 2000 RPM, Tier 4 Final. 4-cycle, 4-cylinder in line, common rail, direct injection, variable geometry turbocharged, intercooled diesel. Low emission engine designed to designed to comply with US EPA emission standard.
HYDRAULICS	Variable flow load sensing system with on demand and servo operated multi-function open center control. independent servo gear pump.
OPERATORS AREA	JCB Command Plus Cab. Climate controlled, noise and vibration by four hydraulically damped resilient mountings. Full opening front window. Fan forced fresh air ventilation with defogger and Fully adjustable, high back air suspension seat with seatbelt, headrest, armrests and backrest recline. Two boom and two mainframe work
CONTROLS	Excavator controls are ISO pattern, servo operated, with in cab 7.0" digit display and change over control to SAE. Tracks are individually operated by foot pedal or hand lever. Speed selection via joystick operated switch. Control isolation by gate lock lever at cab entrance and a console mounted switch. Rearview camera standard.
UPPER	Monoboom with choice of dipper arms to suit dig depth requirements. No reinforcing required for hammer operations. Boom: 18' 8" (5.70m). Dippers: 7' 10" (2.40m), 9' 10" (3.0m).
UNDERCARRIAGE	The long undercarriage gives excellent stability, is a fully welded X-frame type with flush fitted, heavy duty swing turret cover and heavy duty undercover. Two top and eight bottom rollers are sealed and Track idler is sealed and lubricated and incorporates spring cushion recoil. heavy duty track motor guards. Final drives are planetary reduction type with bolt on sprockets. Maximum track speed is 3.5 MPH, low speed is 2.0 MPH. Parking brake is disc type, spring applied, hydraulic release.
ELECTRICAL	24 volt electrical system. 2 x 12 volt heavy duty batteries, 24 volt, 100 amp output alternator with 12 volt in-cab supply.
OPERATING WEIGHT	Equipped with standard boom, 7' 10" (2.40m) dipper, 31" track shoes and excavator bucket: aprx. 57,190 lbs.



245XR Large Excavator



U.S. Dollar Price Page

Effective: Jan 01, 2023

F.O.B. Savannah, GA

SECTION I - YELLOW SERIES

Select one of the following machine Package Build(s).

If none of the Package Build combinations meet your requirements, please order a machine using the Custom Build Sections following.

SALES CODE	ITEM	LIST PRICE
9822	245XR LC MONO STAGE IV/TIER 4 FINAL	\$229,053
900BF01	800MM (31IN) TRACK PLATES TRIPLE GROUSER, 49 LINKS HD	\$11,233
900CF07	MONOBOOM,0 HBCV, 3.0M DIPPER	\$2,501
900DC11	TIPPING LINK- 17 TONNE LUG TIPPING LINK ONLY	\$671
900EF14	USA LANGUAGE PACK (INCLUDES: TRAVEL ALARM, DIPPER LIMITER, ISO/SAE CHANGOVER VALVE)	\$0
900TF38	US & CANADA HYDRAULIC PACK 3.0M DIPPER	\$4,963

LIST PRICE **\$248,421**



245XR Large Excavator



U.S. Dollar Price Page

Effective: Jan 01, 2023

F.O.B. Savannah, GA

SECTION 2 - NEW CUSTOM FACTORY BUILT ORDERS

If a Package Build machine from Section 1 will not meet your requirements, please order a machine by selecting one code from each category below. Select Options from Section 3 as needed.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	PRIMARY BUILD	LIST PRICE
UNDERCARRIAGE		
900AF01	LONG CARRIAGE 2390MM (94IN) GAUGE 4460MM (176IN) LONG	\$0
TRACK PLATES		
900BF01	800MM (31IN) TRACK PLATES TRIPLE GROUSER, 49 LINKS HD	\$11,233
900BF03	600MM (24IN) TRACK PLATES, TRIPLE GROUSER, HD	\$5,341
900BF04	700MM (28IN) TRACK PLATES TRIPLE GROUSER, 49 LINKS HD	\$7,485
MONO BOOM AND DIPPER		
900CF07	MONOBOOM, 0 HBCV, 3.0M DIPPER	\$2,501
TIPPING LINK		
900DC11	TIPPING LINK- 17 TONNE LUG TIPPING LINK ONLY	\$671
LANGUAGE PACK		
900EF14	USA LANGUAGE PACK (INCLUDES: TRAVEL ALARM, DIPPER LIMITER, ISO/SAE CHANGOVER VALVE)	\$0
900EF15	CANADIAN LANGUAGE PACK (INCLUDES: TRAVEL ALARM, DIPPER LIMITER, ISO/SAE CHANGOVER VALVE)	\$0



245XR Large Excavator



U.S. Dollar Price Page

Effective: Jan 01, 2023

F.O.B. Savannah, GA

SECTION 3 - OPTIONS - NEW CUSTOM FACTORY BUILT ORDERS

Select Optional Equipment as desired, within limitations if indicated.

SALES CODE	HYDRAULIC OPTIONS	LIST PRICE
900TF38	US & CANADA HYDRAULIC PACK 3.0M DIPPER	\$4,963
900VA01	HP68 HYDRAULIC OIL- FOR HOT CLIMATE OPERATION	\$0
900VA02	JCB BIO OIL	\$6,368
900VA03	PANOLIN HYDRAULIC OIL	\$10,416
900XA05	BSP - CONVERTER FITTING FOR HIGH FLOW HYDRAULIC	\$134
MACHINE PROTECTION		
900J007	VANDAL GUARDS	\$3,161
900SC03	FOPS FRONT GUARD	\$3,133
900SC04	FOPS ROOF GUARD	\$4,699
EXCAVATOR AND BUCKET OPTIONS		
900L125	GENERAL PURPOSE BUCKET, 1200MM (48IN) WIDE, 0.96m3 HEAPED CAPACITY	\$8,723
900L150	GENERAL PURPOSE BUCKET, 613MM (24") WIDE, 0.35m3 HEAPED ISO CAPACITY	\$6,480
900L152	GENERAL PURPOSE BUCKET, 918MM (36") WIDE, 0.66m3 HEAPED ISO CAPACITY	\$7,912
900L414	DITCHING & GRADING BUCKET 2134MM (79") WIDE, 0.99m3 HEAPED ISO CAPACITY	\$5,724
900L427	BUCKET: DITCHING, GRADING 1.8 M WIDE, 0.50m3 HEAPED CAPACITY	\$7,530
900L428	BUCKET: DITCHING, GRADING, 2.0 M WIDE, 0.55m3 HEAPED CAPACITY	\$6,184