

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

4 6 - 5 4 G V W C H A S S I S S P E C S

Description
Price Level
WST 47X/49X PRL-29X (EFF:MY26 ORDERS)
Data Version
SPECPRO21 DATA RELEASE VER 008
Vehicle Configuration
WESTERN STAR 47X 2026 MODEL YEAR SPECIFIED SET FORWARD AXLE - TRUCK TRAILER TOWING PROVISION AT END OF FRAME WITH SAE J560, WITHOUT END OF FRAME AIR CONNECTIONS LH PRIMARY STEERING LOCATION
General Service
TRUCK CONFIGURATION DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES) EPA EMISSIONS CERTIFICATION FOR REGISTRATION IN EPA OR ACT STATES - EPA CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD OF DRIVER DOOR) CONSTRUCTION SERVICE CONSTRUCTION BUSINESS SEGMENT DIRT/SAND/ROCK COMMODITY TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS MAXIMUM 8% EXPECTED GRADE SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE WESTERN STAR VOCATIONAL WARRANTY

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

EXPECTED FRONT AXLE(S) LOAD : 14000.0 lbs
EXPECTED REAR DRIVE AXLE(S) LOAD :
40000.0 lbs
EXPECTED GROSS VEHICLE WEIGHT CAPACITY
: 54000.0 lbs

Truck Service

DURACCLASS (TBEI)

Engine

CUM L9 260 HP @ 2200 RPM; 2200 GOV RPM,
860 LB-FT @ 1200 RPM

Electronic Parameters

75 MPH ROAD SPEED LIMIT
PTO MODE ENGINE RPM LIMIT - 1600 RPM
PTO RPM WITH CRUISE SET SWITCH - 700 RPM
PTO RPM WITH CRUISE RESUME SWITCH - 700
RPM
ONE PTO SPEED VIA DASH SWITCH
PTO SPEED 1 SETTING - 700 RPM
PTO MINIMUM RPM - 700
PTO 1, DASH SWITCH, ENGAGE BEFORE
DRIVING

Engine Equipment

EPA 2010/GHG 2024 CONFIGURATION
STANDARD OIL PAN
ENGINE MOUNTED OIL CHECK AND FILL
SIDE OF HOOD AIR INTAKE WITH ENGINE
MOUNTED AIR CLEANER
DR 12V 160 AMP 28-SI QUADRAMOUNT PAD
ALTERNATOR WITH REMOTE BATTERY VOLT
SENSE
(3) DTNA GENUINE, FLOODED STARTING, MIN
3000CCA, 555RC, THREADED STUD BATTERIES
BATTERY BOX WITH ALUMINUM COVER
MOUNTED SHORT SIDE TO RAIL
SINGLE BATTERY BOX FRAME MOUNTED LH
SIDE BACK OF CAB
WIRE GROUND RETURN FOR BATTERY CABLES
WITH ADDITIONAL FRAME GROUND RETURN
POLISHED ALUMINUM WST BATTERY BOX
COVER

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

NON-ESSENTIAL POSITIVE LOAD DISCONNECT,
IN CAB CONTROL SWITCH MOUNTED
OUTBOARD OF DRIVER SEAT

POSITIVE AND NEGATIVE POSTS FOR
JUMPSTART LOCATED ON FRAME NEXT TO
STARTER

CUMMINS TURBOCHARGED 18.7 CFM AIR
COMPRESSOR WITH INTERNAL SAFETY VALVE

ELECTRONIC ENGINE INTEGRAL SHUTDOWN
PROTECTION SYSTEM

C-BRAKE BY JACOBS WITH LOW/OFF/HIGH
BRAKING DASH SWITCH

RH OUTBOARD UNDER STEP MOUNTED
HORIZONTAL AFTERTREATMENT SYSTEM
ASSEMBLY WITH RH B-PILLAR MOUNTED
VERTICAL TAILPIPE

ENGINE AFTERTREATMENT DEVICE,
AUTOMATIC OVER THE ROAD REGENERATION
AND VIRTUAL REGENERATION REQUEST
SWITCH IN CLUSTER

11 FOOT 06 INCH (138 INCH+0/-5.9 INCH)
EXHAUST SYSTEM HEIGHT

30 DEGREE CURVE BRIGHT UPPER STACK(S)
AND ELBOW(S)

RH CURVED VERTICAL TAILPIPE B-PILLAR
MOUNTED ROUTED FROM STEP

13 GALLON DIESEL EXHAUST FLUID TANK
POLISHED ALUMINUM WST DIESEL EXHAUST
FLUID TANK COVER

LH HEAVY DUTY STANDARD DIESEL EXHAUST
FLUID TANK LOCATION

STANDARD DIESEL EXHAUST FLUID TANK CAP
PERFORATED SINGLE STAINLESS STEEL
MUFFLER/TAILOPIPE SHIELD WITH WESTERN
STAR LOGO

AIR POWERED ON/OFF ENGINE FAN CLUTCH
AUTOMATIC FAN CONTROL WITH DASH
SWITCH AND INDICATOR LIGHT, NON ENGINE
MOUNTED

DETROIT FUEL/WATER SEPARATOR WITH
WATER IN FUEL SENSOR

CUMMINS SPIN ON FUEL FILTER

FULL FLOW OIL FILTER

1400 SQUARE INCH VOCATIONAL RADIATOR
ANTIFREEZE TO -34F, OAT (NITRITE AND
SILICATE FREE) EXTENDED LIFE COOLANT

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

GATES BLUE STRIPE COOLANT HOSES OR
EQUIVALENT
STANDARD CHARGE AIR COOLER PLUMBING
RADIATOR DRAIN VALVE
LOWER RADIATOR GUARD
NO REPTO, EXTENDED FLYWHEEL HOUSING,
CUMMINS REQUIRED FOR PACKAGING
PHILLIPS-TEMRO 1000 WATT/115 VOLT BLOCK
HEATER
PHILLIPS-TEMRO 300 WATT/115 VOLT OIL
PREHEATER
CHROME ENGINE HEATER RECEPTACLE
MOUNTED UNDER LH DOOR
ELECTRIC GRID AIR INTAKE WARMER
DELCO 12V 39MT HD/OCP STARTER WITH
THERMAL PROTECTION AND INTEGRATED
MAGNETIC SWITCH

Transmission

ALLISON 3000 RDS AUTOMATIC TRANSMISSION
WITH PTO PROVISION

Transmission Equipment

ALLISON VOCATIONAL PACKAGE 223 -
AVAILABLE ON 3000/4000 PRODUCT FAMILIES
WITH VOCATIONAL MODELS RDS, HS, MH AND
TRV
ALLISON VOCATIONAL RATING FOR CONCRETE
MIXER APPLICATIONS ONLY AVAILABLE WITH
3000 PRODUCT FAMILIES
PRIMARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY
SECONDARY MODE GEARS, LOWEST GEAR 1,
START GEAR 1, HIGHEST GEAR 6, AVAILABLE
FOR 3000/4000 PRODUCT FAMILIES ONLY
PRIMARY SHIFT SCHEDULE RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE
SECONDARY SHIFT SCHEDULE
RECOMMENDED BY DTNA AND ALLISON, THIS
DEFINED BY ENGINE AND VOCATIONAL USAGE
PRIMARY SHIFT SPEED RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE
SECONDARY SHIFT SPEED RECOMMENDED BY
DTNA AND ALLISON, THIS DEFINED BY ENGINE
AND VOCATIONAL USAGE

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH CAP
ELECTRONIC TRANSMISSION WIRING TO CUSTOMER INTERFACE CONNECTOR
CUSTOMER INSTALLED CHELSEA 489 SERIES PTO
PTO MOUNTING, BOTTOM OF MAIN TRANSMISSION DETROIT & EATON FULLER TRANSMISSION
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN
HEAVY DUTY ELECTRONIC TRANSMISSION SHIFT CONTROL, COLUMN MOUNTED
WATER TO OIL TRANSMISSION COOLER
TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)

Front Axle and Equipment

DETROIT DA-F-14.7-3 14,700# FF1 71.5 KPI/3.74
DROP SINGLE FRONT AXLE
CONMET PRESET PLUS PREMIUM IRON FRONT HUBS
MERITOR 16.5X5 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES
NON-ASBESTOS FRONT BRAKE LINING
CONMET CAST IRON FRONT BRAKE DRUMS
FRONT BRAKE DUST SHIELDS
FRONT OIL SEALS
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS
SINGLE HIGH CAPACITY POWER STEERING GEAR, BENDIX, 14.6-18K
2 QUART SEE THROUGH POWER STEERING RESERVOIR
CURRENT AVAILABLE SYNTHETIC 75W-90
FRONT AXLE LUBE

Front Suspension

14,600# TAPERLEAF FRONT SUSPENSION

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

MAINTENANCE FREE RUBBER BUSHINGS -
FRONT SUSPENSION
FRONT SHOCK ABSORBERS

Rear Axle and Equipment

MERITOR MT-40-14X 40,000# R-SERIES TANDEM
REAR AXLE
CONMET PRESET PLUS PREMIUM IRON REAR
HUBS
3.90 REAR AXLE RATIO
IRON REAR AXLE CARRIER WITH OPTIONAL
HEAVY DUTY AXLE HOUSING
SPL170 XL DANA SPICER MAIN DRIVELINE WITH
HALF ROUND YOKES
SPL170 XL DANA SPICER INTERAXLE
DRIVELINE WITH HALF ROUND YOKES
DRIVER CONTROLLED TRACTION
DIFFERENTIAL - BOTH TANDEM REAR AXLES
(1) INTERAXLE LOCK VALVE, (1) DRIVER
CONTROLLED DIFFERENTIAL LOCK FORWARD-
REAR AND REAR-REAR AXLE VALVE
INDICATOR LIGHT FOR EACH INTERAXLE
LOCKOUT SWITCH
INDICATOR LIGHT FOR EACH DIFFERENTIAL
LOCKOUT SWITCH
MERITOR 16.5X8.62 Q+ CAST SPIDER CAM
REAR BRAKES, DOUBLE ANCHOR, FABRICATED
SHOES
NON-ASBESTOS REAR BRAKE LINING
BRAKE CAMS AND CHAMBERS ON FORWARD
SIDE OF DRIVE AXLE(S)
GUNITE CAST IRON REAR BRAKE DRUMS
NO REAR BRAKE DUST SHIELDS
REAR OIL SEALS
WABCO TRISTOP D LONGSTROKE 2-DRIVE
AXLE SPRING PARKING CHAMBERS
HALDEX AUTOMATIC REAR SLACK ADJUSTERS
CURRENT AVAILABLE SYNTHETIC 75W-90 REAR
AXLE LUBE
STANDARD REAR AXLE BREATHER(S)

Rear Suspension

TUFTRAC GEN2 40,000# REAR SPRING
SUSPENSION

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

9.5 INCH NOMINAL RIDE HEIGHT (460MM
GLOBAL REFERENCE HEIGHT)
AXLE CLAMPING GROUP
55 INCH AXLE SPACING
FORE/AFT AND TRANSVERSE CONTROL RODS
REAR SHOCK ABSORBERS - ONE AXLE

Pusher / Tag Equipment

NO PUSHER/TAG BRAKE DUST SHIELDS

Brake System

WABCO 4S/4M ABS WITH TRACTION CONTROL
WITH ATC SHUT OFF SWITCH
REINFORCED NYLON, FABRIC BRAID AND WIRE
BRAID CHASSIS AIR LINES
RELAY VALVE WITH 5-8 PSI CRACK PRESSURE,
NO REAR PROPORTIONING VALVE
WABCO SYSTEM SAVER HP WITH INTEGRAL
AIR GOVERNOR AND HEATER
AIR DRYER MOUNTED INBOARD ON LH RAIL
STEEL AIR BRAKE RESERVOIRS
PULL CABLES ON ALL AIR RESERVOIR(S)

Trailer Connections

PRIMARY CONNECTOR/RECEPTACLE WIRED
FOR SEPARATE STOP/TURN, ABS CENTER PIN
POWERED THROUGH IGNITION
SAE J560 7-WAY PRIMARY TRAILER CABLE
RECEPTACLE MOUNTED END OF FRAME
NO TRAILER ELECTRICAL CABLE

Wheelbase & Frame

5390MM (212 INCH) WHEELBASE, SFA ONLY
9.0MM X 83.0MM X 283.0MM STEEL FRAME
(0.35X3.35X11.14 INCH) 120 KSI
2025MM (80 INCH) REAR FRAME OVERHANG
FRAME OVERHANG RANGE: 71 INCH TO 80
INCH
CALC'D BACK OF CAB TO REAR SUSP C/L (CA) :
130.71 in
CALC'D FRAME LENGTH - OVERALL : 320.72 in
FRAME HEIGHT TOP FRONT UNLADEN : 43.78 in
FRAME HEIGHT TOP FRONT LADEN : 40.79 in
FRAME HEIGHT TOP REAR UNLADEN : 42.79 in
FRAME HEIGHT TOP REAR LADEN : 40.63 in

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

SQUARE END OF FRAME
STANDARD WEIGHT ENGINE CROSSMEMBER
STANDARD CAST ALUMINUM CROSSMEMBER
BACK OF TRANSMISSION
STANDARD CAST ALUMINUM MIDSHIP
STANDARD CAST ALUMINUM REARMOST
CROSSMEMBER
STANDARD SUSPENSION CROSSMEMBER
CAST ALUMINUM REAR SUSPENSION
CROSSMEMBER

Chassis Equipment

POLISHED ALUMINUM WST EQUIPMENT
COVERS
PAINTED STEEL 3/16 INCH (7GA) VOCATIONAL
BUMPER
REMOVABLE FRONT TOW/RECOVERY
DEVICE, STORED ON CHASSIS FRAME
BUMPER MOUNTING FOR SINGLE LICENSE
PLATE
CLASS 10.9 THREADED METRIC FASTENERS
EXTERIOR HARNESSSES WRAPPED IN
ABRASION TAPE
UPFIT ROUTING AND CLIPPING BRACKET, LH,
BOC TO SUSPENSION, UPPER & LOWER
SUPPORTS
UPFIT ROUTING AND CLIPPING BRACKET, RH,
BOC TO SUSPENSION, UPPER & LOWER
SUPPORTS

Fuel Tanks

80 GALLON/302 LITER ALUMINUM FUEL TANK -
LH
25 INCH DIAMETER FUEL TANK(S)
POLISHING OF FUEL/HYDRAULIC TANK(S) WITH
PAINTED BANDS
FUEL TANK(S) FORWARD
PLAIN STEP FINISH
CHROME FUEL TANK CAP(S)
EQUIFLO INBOARD FUEL SYSTEM
HIGH TEMPERATURE REINFORCED NYLON
FUEL LINE

Tires

CONTINENTAL HAU 3 WT 315/80R22.5 20 PLY
RADIAL FRONT TIRES

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description
CONTINENTAL INTELLIGENT HDC3 11R22.5 16 PLY RADIAL REAR TIRES
Wheels
ACCURIDE 29039 22.5X9.00 10-HUB PILOT 5.25 INSET 5-HAND STEEL DISC FRONT WHEELS MAXION WHEELS 91262 22.5X8.25 10-HUB PILOT 5-HAND STEEL DISC REAR WHEELS FRONT WHEEL MOUNTING NUTS REAR WHEEL MOUNTING NUTS
Cab Exterior
111.6 INCH BBC CONVENTIONAL ALUMINUM CAB STAINLESS STEEL CAB ACCENT MOLDING FRONT FENDERS BOLT-ON MOLDED FLEXIBLE FENDER EXTENSIONS INTERIOR GRAB HANDLES WITH ADDED LOWER LH AND RH A PILLAR GRAB HANDLES AND LH AND RH EXTERIOR NON-SLIP GRAB HANDLES BRIGHT HOOD MOUNTED AIR INTAKE GRILLE, BLACK SCREEN, WITH LED ACCENT LIGHTS X-SERIES STEEL REINFORCED ALUMINUM CAB X-SERIES VOCATIONAL HOOD HOOD OPENING ASSIST WITH LOCKING STRUT WESTERN STAR NAMEPLATES DUAL HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS SINGLE ELECTRIC HORN REAR LICENSE PLATE MOUNT END OF FRAME SWITCH, INDICATOR LIGHT AND WIRING FOR (2) CUSTOMER FURNISHED BEACONS DUAL STAGE INTELLIGENT LED HEADLIGHTS WITH HEATED LENS SYSTEM ROOF MOUNTED LED MARKER LIGHTS DAYTIME RUNNING LIGHTS INTEGRAL LED STOP/TAIL/BACKUP LIGHTS LED SIDE TURN SIGNAL C-BAR MIRROR SYSTEM WITH DUAL HEATED MIRRORS WITH INTEGRAL HEATED CONVEX, DUAL REMOTE, STAINLESS STEEL BACK COVER, AND BLACK C-BAR 102 INCH EQUIPMENT WIDTH

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

LH AND RH CONVEX MIRRORS INTEGRAL WITH
PRIMARY MIRRORS
RH DOWN VIEW MIRROR
STANDARD SIDE/REAR REFLECTORS
REAR REFLECTIVE DEVICE
POLISHED ALUMINUM WST AFTERTREATMENT
SYSTEM COVER
NO SLEEPER VENT
SINGLE SOLAR TINTED REAR WINDOW, (1) 31
INCH X 20 INCH
1-PIECE ROPED-IN SOLAR GREEN GLASS
WINDSHIELD
8 LITER (2 GAL) WINDSHIELD WASHER
RESERVOIR, CAB MOUNTED, WITH FLUID
LEVEL INDICATOR

Cab Interior

X-SERIES BASE INTERIOR TRIM LEVEL
PACKAGE
CHARCOAL BLACK VINYL BASE LEVEL
INTERIOR
CARBON WITH BASE BLACK ACCENT
BLACK MATS WITH ADDED FLOOR HEAT AND
NOISE INSULATION
(2) DASH MOUNTED POWER OUTLETS AND
COIN TRAY
FORWARD ROOF MOUNTED CONSOLE
LH AND RH DOOR STORAGE POCKETS
INTEGRATED INTO MOLDED DOOR PANELS
(2) COAT HOOKS ON BACKWALL OF CAB
NO UPPER BUNK
DIGITAL ALARM CLOCK IN DRIVER DISPLAY
2-1/2 LB. FIRE EXTINGUISHER MOUNTED
INBOARD OF DRIVER SEAT
STANDARD HEATER PLUMBING WITH BALL
SHUTOFF VALVES AT SUPPLY LINES ONLY
RADIATOR MOUNTED AIR CONDITIONER
CONDENSER
STANDARD INSULATION
STANDARD LED CAB LIGHTING
REMOTE KEYLESS ENTRY AND 2
TRANSMITTERS
DOOR LOCKS AND IGNITION SWITCH KEYED
THE SAME

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

KEY QUANTITY OF 4
LH AND RH ELECTRIC DOOR LOCKS WITH
AUTO UNLOCK FEATURE WHEN DOOR IS SET
FROM OPEN TO CLOSED POSITION
BRIGHT DOOR HANDLES
NO MATTRESS
TRIANGULAR REFLECTORS WITHOUT FLARES
PREMIUM 2.0 HIGH BACK AIR SUSPENSION
DRIVER SEAT WITH 2 AIR LUMBAR,
INTEGRATED CUSHION EXTENSION, TILT AND
ADJUSTABLE SHOCK
PREMIUM 2.0 HIGH BACK AIR SUSPENSION
PASSENGER SEAT WITH 2 AIR LUMBAR,
INTEGRATED CUSHION EXTENSION, TILT AND
ADJUSTABLE SHOCK
DUAL DRIVER SEAT ARMRESTS, NO
PASSENGER SEAT ARMRESTS
BLACK VINYL DRIVER SEAT COVER WITH NO
LOGO
BLACK VINYL PASSENGER SEAT COVER WITH
NO LOGO
3 POINT HIGH VISIBILITY ORANGE ADJUSTABLE
D-RING RETRACTOR DRIVER AND FIXED D-RING
RETRACTOR PASSENGER SEAT BELTS
ADJUSTABLE TILT AND TELESCOPING
STEERING COLUMN
4-SPOKE 18 INCH (450MM) BLACK STEERING
WHEEL WITH SWITCHES
DRIVER AND PASSENGER INTERIOR SUN
VISORS

Instruments & Controls

STANDARD FOOT PEDAL SYSTEM
ELECTRONIC ACCELERATOR CONTROL
ENGINE REMOTE INTERFACE WITH PARK
BRAKE INTERLOCK
BLACK GAUGE BEZELS
STANDARD CENTER INSTRUMENT PANEL
DUAL NEEDLE PRIMARY AND SECONDARY AIR
PRESSURE GAUGE
INTAKE MOUNTED AIR RESTRICTION
INDICATOR WITHOUT GRADUATIONS
ELECTRONIC CRUISE CONTROL WITH
CONTROLS ON STEERING WHEEL SPOKES

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

KEY OPERATED IGNITION SWITCH AND
INTEGRAL START POSITION; 4 POSITION
OFF/RUN/START/ACCESSORY

PREMIUM INSTRUMENT CLUSTER WITH 5.0
INCH TFT COLOR DISPLAY

DIGITAL PANEL LAMP DIMMER SWITCH IN
DRIVER DISPLAY

HEAVY DUTY ONBOARD DIAGNOSTICS
INTERFACE CONNECTOR WITH DUST CAP
LOCATED BELOW LH DASH

2 INCH ELECTRIC FUEL GAUGE

ENGINE REMOTE INTERFACE WITH ONE OR
MORE SET SPEEDS

ELECTRICAL ENGINE COOLANT TEMPERATURE
GAUGE

NO ENGINE OIL TEMPERATURE GAUGE

ELECTRIC ENGINE OIL PRESSURE GAUGE

2 INCH TRANSMISSION OIL TEMPERATURE
GAUGE

ELECTRONIC OUTSIDE TEMPERATURE
SENSOR DISPLAY IN DRIVER MESSAGE
CENTER

ENGINE AND TRIP HOUR METERS INTEGRAL
WITHIN DRIVER DISPLAY

PTO CONTROLS FOR ENHANCED VEHICLE
ELECTRIC/ELECTRONIC ARCHITECTURE

NO OBSTACLE DETECTION SYSTEM

NO DR ASSIST SYSTEM

NO VEHICLE STABILITY ADVISOR OR CONTROL

NO LANE DEPARTURE WARNING SYSTEM

TMC RP1226 ACCESSORY CONNECTOR
LOCATED BEHIND PASSENGER SIDE
REMOVEABLE DASH PANEL

TOP OF DASH RAM MOUNT WITHOUT POWER
OR GROUND, FOR CUSTOMER FURNISHED
DEVICE

AM/FM/WB WORLD TUNER RADIO WITH
BLUETOOTH, USB AND AUXILIARY INPUTS,
J1939

DASH MOUNTED RADIO

STANDARD SPEAKER SYSTEM

NO AM/FM RADIO ANTENNA

POWER AND GROUND WIRING PROVISION
OVERHEAD

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description

ROOF/OVERHEAD CONSOLE CB RADIO
PROVISION
SINGLE REMOTE SPEAKER WITH LEAD FOR 2-
WAY RADIO
SINGLE FIBERGLASS LH MIRROR MOUNTED CB
ANTENNA WITH BRACKET AND LEAD
HEADLINER MULTI-BAND ANTENNA:
AM/FM/WEATHERBAND, WIFI/BLUETOOTH,
GNSS/GPS
NO DIGITAL SATELLITE AUDIO RECEIVER
ANTENNA
ELECTRONIC MPH SPEEDOMETER WITH
SECONDARY KPH SCALE, WITHOUT
ODOMETER
ELECTRONIC 2500 RPM TACHOMETER
DETROIT CONNECT PLATFORM HARDWARE
5 YEARS DAIMLER CONNECTIVITY BASE
PACKAGE (FEATURES VARY BY MODEL)
POWERED BY DETROIT CONNECT ON
CUMMINS ENGINES
NO ASE DATA SVCE EXTENSION
IGNITION SWITCH CONTROLLED ENGINE STOP
FOUR EXTRA HARDWIRED SWITCHES IN DASH,
ROUTE TO UNDER CAB, CAPPED
HARDWIRE SWITCH #1, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #2, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #3, ON/OFF LATCHING, 10
AMPS BATTERY POWER
HARDWIRE SWITCH #4, ON/OFF LATCHING, 10
AMPS BATTERY POWER
PRE-TRIP INSPECTION FEATURE FOR
EXTERIOR LAMPS ONLY
REAR SPRING LOADED HAND CONTROL BRAKE
VALVE
DIGITAL TURBO AIR PRESSURE IN DRIVER
DISPLAY
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH
DRIVER DISPLAY
ROTARY HEADLAMP SWITCH, MARKER
LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT
FOR OPTIONAL FOG/ROAD LAMPS
ONE VALVE PARKING BRAKE SYSTEM WITH
WARNING INDICATOR

Prepared for:
CINI ZACHARIA
OKLAHOMA STATE OF
5005 N LINCOLN BLVD
OKLAHOMA CITY, OK 73105
Phone: 405-521-2116

Prepared by:
Mike Sartin
PREMIER TRUCK GROUP OF
TULSA
5104 W. 60TH STREET
TULSA, OK 74107
Phone: 918-445-5300 ext 4061

Description	
	SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASH/WIPE/INTERMITTENT QUICKFIT POWERTRAIN INTERFACE CONNECTOR UNDER CAB WITH BLUNTCUTS
Design	
	PAINT: ONE SOLID COLOR
Color	
	CAB COLOR A: L0006EY WHITE ELITE EY BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT POWDER WHITE (N0006EA) FRONT WHEELS/RIMS (PKWHT21, TKWHT21, W, TW) POWDER WHITE (N0006EA) REAR WHEELS/RIMS (PKWHT21, TKWHT21, W, TW) BUMPER PAINTED SAME AS CHASSIS
Certification / Compliance	
	U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS
Extended Warranty	
	TOWING: 2 YEARS/UNLIMITED MILES/KM EXTENDED TOWING COVERAGE \$750 CAP FEX APPLIES

(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.