

# Minimum Standards for Communication Equipment Purchases



November 4<sup>th</sup>, 2009

Version 1.01

## Table of Contents

1	Introduction .....	3
2	Methodology.....	4
3	Phase I: Subscribers .....	5
3.1	VHF (Low Band) Radio (33 MHz – 50 MHz).....	5
3.1.1	Simplex VHF (Low Band) Interoperability Channels .....	6
3.2	VHF (High Band) Radio (150 – 162 MHz) .....	6
3.2.1	Simplex VHF (High Band) Interoperability Channels.....	7
3.3	Minimum Requirements for UHF Radio Equipment (450 – 470 MHz) .....	7
3.3.1	Repeated UHF Interoperability Channels .....	8
3.3.2	Simplex UHF Interoperability Channels .....	8
3.4	Minimum Requirements for 800 MHz Radio Equipment (806 – 870 MHz) Pre-Rebanding .....	8
3.4.1	Repeated 800 MHz Interoperability Channels (Pre-Rebanding).....	9
3.4.2	Simplex 800 MHz Interoperability Channels (Pre-Rebanding).....	9
3.5	Minimum Requirements for 800 MHz Radio Equipment (806 – 870 MHz) Post Rebanding.....	10
3.5.1	Repeated 800 MHz Interoperability Channels (Rebanded) .....	10
3.5.2	Simplex 800 MHz Interoperability Channels (Rebanded) .....	11
3.6	Communication Equipment Accessories .....	11



Record of Version		

## 1 Introduction

The lack of adequate, reliable, and interoperable communications systems has been a challenge for public safety agencies in the state of Oklahoma and across the country for decades. In many cases, agencies cannot perform their mission-critical duties effectively, because they are unable to communicate vital voice or data information inter-jurisdictionally in daily operations or in emergency situations.

In the state of Oklahoma, cultural resistance to change and limited funding has held the communications capabilities of most agencies well behind the current standard and has caused systems to be developed independently of one another. In order to resolve some of these issues and create a more formalized process for communications interoperability planning, the Oklahoma Legislature passed Senate Bill 1153 (SB 1153) in early 2009.

SB 1153 is critical to communications interoperability efforts in the state of Oklahoma for several reasons: First, it names the Oklahoma Office of Homeland Security (OKOHS) as a central point of contact for all statewide communications interoperability planning. Next, SB 1153 enumerates the planning duties for OKOHS. These duties include:

1. Oversight and implementation of the Statewide Communications Interoperability Plan (SCIP);
2. Coordination of a migration plan for use of communications interoperability technologies including aid to connect disparate systems used by public safety agencies; and
3. Assistance with applying for, receiving, and holding authorization for frequencies and channels for state agencies.

Essentially, SB 1153 makes communications interoperability efforts a priority in the state of Oklahoma.

One of the most important aspects of SB 1153 is that it gives OKOHS the ability to create standards for future purchases of equipment and infrastructure made by state agencies in support of communications interoperability in Oklahoma. The goal of these standards is to eliminate redundancy and ensure the compatibility of new purchases with existing technology.

## 2 Methodology

OKOHS recently formalized the Interoperable Communications State Standards (IOCSS) Working Group. The IOCSS is composed of representatives from multiple state agencies to recommend minimum standards for communication equipment purchases. It was imperative to include multiple agencies with a vested interest in communications interoperability to ensure the success of these minimum standards.

The IOCSS will meet as needed to establish and modify minimum standards for communication equipment.

To comply with the November 1<sup>st</sup>, 2009 deadline, OKOHS proposes that the standards be implemented in the following phases:

Phase 1: Implement Subscriber Equipment Standards (Includes Mobile and Portable Radios)<sup>1</sup>

Phase 2: Implement Repeater Equipment Standards (Best practices)

Phase 3: Implement Infrastructure Standards (Tower Sites)

Phase 4: Implement Tactical Communications Equipment Standards (Gateways)

Phase 5: Implement Data Connectivity Standards

Additional information will be added to this document as minimum standards are defined for the forthcoming phases. It is imperative to note that this document is considered to be a living document and will be updated as new information becomes available.

### **3 Phase I: Subscribers**

The following minimum standards for subscriber equipment have been defined for VHF (Low Band), VHF (High Band), UHF and 800 MHz radio equipment. All equipment purchases must adhere to the technical requirements defined below. At a minimum, each radio must be programmed with the applicable interoperability frequencies as defined below for each frequency band.

#### **3.1 VHF (Low Band) Radio (33 MHz – 50 MHz)**

VHF (Low Band) equipment can only be purchased to support existing VHF (Low Band) communication systems. OKOHS strongly discourages any state agency from purchasing a new VHF (Low Band) system without justifiable cause.

All new purchases of VHF (Low Band) radio equipment must adhere to the following minimum requirements:

- Federal Communications Commission (FCC) Part 90 Type Accepted
- Capable Continuous Tone-Coded Squelch System (CTCSS)
- Minimum of 12 character alpha numeric display
- Minimum of 60 watts power for all mobile radio equipment
- Minimum of 4 watts for all portable radio equipment
- Minimum of 32 channels
- In compliance with Mil Spec 810 C, 810 D and 810 E

---

<sup>1</sup> Phase 1 is currently available at [http://www.ok.gov/homeland/Interoperable\\_Communications/Standards/](http://www.ok.gov/homeland/Interoperable_Communications/Standards/)

- Programmed with the Non-Federal VHF low band National Interoperability Frequencies as defined in the VHF low band tables listed below

To date, the state of Oklahoma has not licensed the VHF (Low Band) national interoperability frequencies. However, all radios purchased must be programmed with the national interoperability channels as defined by National Public Safety Telecommunications Council’s (NPSTC) Channel Naming Report dated June, 13<sup>th</sup> 2007. Until licensed by the FCC, these frequencies can only be used for the immediate protection of life or property; radio users may use prudent measures beyond the specifics of their license.

### 3.1.1 Simplex VHF (Low Band) Interoperability Channels

Simplex VHF (Low Band) Interoperability Channels for Subscriber Equipment			
Description	NPSTC ID	Channel (MHz)	CTCSS Tone ±
Law Enforcement	LLAW1	39.4600	CSQ*/156.7
Fire (Proposed)	LFIRE2	39.4800	
Law Enforcement	LLAW3	45.8600	
Fire	LFIRE4	45.8800	

±Default operation should be carrier squelch receive, Continuous Tone Coded Squelch System (CTCSS) transmit. If the user can enable/disable without reprogramming the radio, the indicated CTCSS tone should also be programmed for receive, and the user instructed how and when to enable/disable.  
\*Carrier Squelch (CSQ); No sub-audible tone on either the receiver or transmitter.

### 3.2 VHF (High Band) Radio (150 – 162 MHz)

All new purchases of VHF (High Band) radio equipment must adhere to the following minimum requirements:

- FCC Part 90 Type Accepted
- Capable Continuous Tone-Coded Squelch System (CTCSS)
- Narrowband compliant according to FCC emissions 11K2F3E
- Wideband compliant according to FCC emissions 20K0F3E<sup>2</sup>
- Minimum of 12 character alpha numeric display
- Minimum of 120 channels
- Minimum of 25 watts power for all mobile radio equipment
- Minimum of 4 watts for all portable radio equipment
- In compliance with Mil Spec 810 C, 810 D and 810 E
- Programmed with the Non-Federal VHF high band National Interoperability Frequencies as defined in the VHF high band tables listed below

All new VHF (High Band) radio equipment must be programmed with both the national interoperability channels as defined by NPSTC’s Channel Naming Report dated June 13<sup>th</sup>, 2007. The IOCSS strongly

---

<sup>2</sup> All references to wideband emissions will be removed from this document on January 1<sup>st</sup>, 2011.

recommends that all new VHF (High Band) must be programmed with the local mutual aid channels for police, fire and EMS. Any use as a base station, repeater or control station will require an FCC radio license. However, the VHF (High Band) national interoperability channels are covered by a “blanket authorization” from the FCC for mobile operation. Mobile operation is an FCC reference to a radio frequency that is only to be used in a mobile or portable radio. All of the frequencies listed in the tables below are narrowband (11K2F3E) only.

### 3.2.1 Simplex VHF (High Band) Interoperability Channels

Simplex VHF (High Band) Interoperability Channels for Subscriber Equipment*				
Description	Authorized Use	NPSTC ID	Channel (MHz)	CTCSS
Calling	base/mobile	VCALL10	155.7525	CSQ /156.7 (5A)
Tactical	base/mobile	VTAC11	151.1375	CSQ /156.7 (5A)
Tactical	base/mobile	VTAC12	154.4525	CSQ /156.7 (5A)
Tactical	base/mobile	VTAC13	158.7375	CSQ /156.7 (5A)
Tactical	base/mobile	VTAC14	159.4725	CSQ /156.7 (5A)
Description	Authorized Use	Channel ID	Channel (MHz)	CTCSS
STATE LAW	base/mobile	STATE LAW	155.4900	
STATE FIRE	base/mobile	STATE FIRE	154.1300	
STATE NET	base/mobile	STATE NET	155.6700	
HEAR	base/mobile	HEAR	155.3400	
OK LG MA	base/mobile	OK LG MA	155.7600	

\* To date, the state of Oklahoma has not licensed “State Law,” “State Fire,” “State Net,” “HEAR” and “OK LG MA” mutual aid frequencies statewide for all State agencies. However, all radios purchased must be programmed with the statewide frequencies listed above. Until licensed by the FCC, these frequencies can only be used for the immediate protection of life or property; radio users may use prudent measures beyond the specifics of their license.

### 3.3 Minimum Requirements for UHF Radio Equipment (450 – 470 MHz)

All new purchases of UHF radio equipment must adhere to the following minimum requirements:

- FCC Part 90 Type Accepted
- Capable Continuous Tone-Coded Squelch System (CTCSS)
- Narrowband compliant according to FCC emission 11K2F3E
- Wideband compliant according to FCC emission 20K0F3E<sup>3</sup>
- Minimum of 12 character alpha numeric display
- Minimum of 120 channels
- Minimum of 25 watts power for all mobile radio equipment
- Minimum of 4 watts for all portable radio equipment
- In compliance with Mil Spec 810 C, 810 D and 810 E
- Programmed with the Non-Federal UHF National Interoperability Frequencies as defined in the UHF tables listed below

<sup>3</sup> All references to wideband emissions will be removed from this document on January 1<sup>st</sup>, 2011.

All new UHF radio equipment must be programmed with the national interoperability channels as defined by NPSTC’s Channel Naming Report dated June 13<sup>th</sup>, 2007. Any use as a base station, repeater or control station will require an FCC radio license. However, the UHF national interoperability channels are covered by a “blanket authorization” from the FCC for mobile operation. Mobile operation is an FCC reference to a radio frequency that is only to be used in a mobile or portable radio. All of the frequencies listed in the tables below are narrowband (11K2F3E) only. Usage of any UHF channel in the simplex mode as base stations is preferred over their usage as repeater stations to minimize interference.

### 3.3.1 Repeated UHF Interoperability Channels

Repeated UHF Interoperability Channels for Subscriber Equipment						
Desc	NPSTC ID	CTCSS*	TX Freq	Authorized Use	RX Freq	Authorized Use
Calling	UCALL40	156.7 Hz	458.2125	Mobile Output	453.2125	Mobile Input
Tactical	UTAC41	156.7 Hz	458.4625	Mobile Output	453.4625	Mobile Input
Tactical	UTAC42	156.7 Hz	458.7125	Mobile Output	453.7125	Mobile Input
Tactical	UTAC43	156.7 Hz	458.8625	Mobile Output	453.8625	Mobile Input

\* Default operation should be carrier squelch receive, CTCSS 156.7 transmit. If the user can enable/disable CTCSS without reprogramming the radio, the indicated CTCSS tone should also be programmed for receive, and the user instructed how and when to enable/disable.

### 3.3.2 Simplex UHF Interoperability Channels

Simplex UHF Interoperability Channels for Subscriber Equipment						
Desc	NPSTC ID	CTCSS*	TX Freq	Authorized Use	RX Freq	Authorized Use
Calling	UCALL40D	156.7 Hz	453.2125	Mobile Direct Output	453.2125	Mobile Direct Input
Tactical	UTAC 41D	156.7 Hz	453.4625	Mobile Direct Output	453.4625	Mobile Direct Input
Tactical	UTAC42D	156.7 Hz	453.7125	Mobile Direct Output	453.7125	Mobile Direct Input
Tactical	UTAC43D	156.7 Hz	453.8625	Mobile Direct Output	453.8625	Mobile Direct Input

\* Default operation should be carrier squelch receive, CTCSS 156.7 transmit. If the user can enable/disable CTCSS without reprogramming the radio, the indicated CTCSS tone should also be programmed for receive, and the user instructed how and when to enable/disable.  
D – Denotes low side of the frequency pair in direct (simplex) mode

### 3.4 Minimum Requirements for 800 MHz Radio Equipment (806 – 870 MHz) Pre-Rebanding<sup>4</sup>

- FCC Part 90 Type Accepted
- Equipped with P25 software
- Capable Continuous Tone-Coded Squelch System (CTCSS)
- In Compliance with FCC National Public Safety Planning Advisory Committee (NPSPAC) emissions 16K0F3E and 20K0F3E
- Minimum of 12 character alpha numeric display

<sup>4</sup> This section will be removed from this document upon completion of the 800 MHz rebanding initiative.

- Minimum of 256 channels (talkgroups) for both mobile and portable radios
- Minimum of 10 watts power for all mobile radio equipment
- Minimum of 3 watts for all portable radio equipment
- In compliance with Mil Spec 810 C, 810 D, 810 E and 810 F
- Programmed with the Non-Federal 800 MHz National Interoperability Frequencies as defined in the 800 MHz tables listed below

All new 800 MHz radio equipment must be programmed with both the pre- and post-rebanding national interoperability channels as defined by NPSTC’s Channel Naming Report dated June 13<sup>th</sup>, 2007. Any use as a base station, repeater or control station will require an FCC radio license and approval from Oklahoma NPSPAC Region 34. However, the 800 MHz national interoperability channels are covered by a “blanket authorization” from the FCC for mobile operation. Mobile operation is an FCC reference to a radio frequency that is only to be used in a mobile or portable radio. The FCC is currently in the process of rebanding the 800 MHz radio spectrum across the United States. Oklahoma’s rebanding will begin in 2010 and should be completed within thirty-six (36) months. All pre-rebanding information specific to the 800 MHz spectrum will be removed from this document upon completion of the 800 MHz rebanding initiative.

### 3.4.1 Repeated 800 MHz Interoperability Channels (Pre-Rebanding)

Repeated 800 MHz Interoperability Channels for Subscriber Equipment (Pre-Rebanding) ±						
Desc	NPSTC ID	CTCSS*	TX Freq	Authorized Use	RX Freq	Authorized Use
Calling	ICALL	156.7 Hz	821.0125	Mobile Output	866.0125	Mobile Input
Tactical	ITAC 1	156.7 Hz	821.5125	Mobile Output	866.5125	Mobile Input
Tactical	ITAC 2	156.7 Hz	822.0125	Mobile Output	867.0125	Mobile Input
Tactical	ITAC3	156.7 Hz	822.5125	Mobile Output	867.5125	Mobile Input
Tactical	ITAC4	156.7 Hz	823.0125	Mobile Output	868.0125	Mobile Input
*Default operation should be carrier squelch receive, CTCSS 156.7(5A) transmit. If the user can enable/disable CTCSS without reprogramming the radio, the indicated CTCSS tone should also be programmed for receive, and the user instructed how and when to enable/disable. ± This information will be deleted upon completion of the 800 MHz rebanding initiative currently taking place in Oklahoma.						

### 3.4.2 Simplex 800 MHz Interoperability Channels (Pre-Rebanding)

Simplex 800 MHz Interoperability Channels for Subscriber Equipment (Pre-Rebanding) ±						
Desc	NPSTC ID	CTCSS*	TX Freq	Authorized Use	RX Freq	Authorized Use
Calling	ICALL	156.7 Hz	866.0125	Mobile Direct Output	866.0125	Mobile Direct Input
Tactical	ITAC 1	156.7 Hz	866.5125	Mobile Direct Output	866.5125	Mobile Direct Input
Tactical	ITAC 2	156.7 Hz	867.0125	Mobile Direct Output	867.0125	Mobile Direct Input
Tactical	ITAC3	156.7 Hz	867.5125	Mobile Direct Output	867.5125	Mobile Direct Input
Tactical	ITAC4	156.7 Hz	868.0125	Mobile Direct Output	868.0125	Mobile Direct Input
*Default operation should be carrier squelch receive, CTCSS 156.7(5A) transmit. If the user can enable/disable CTCSS without reprogramming the radio, the indicated CTCSS tone should also be programmed for receive, and the user instructed how and when to enable/disable. D – Denotes low side of the frequency pair in direct (simplex) mode ± This information will be deleted upon completion of the 800 MHz rebanding initiative currently taking						

**Simplex 800 MHz Interoperability Channels for Subscriber Equipment (Pre-Rebanding) ±**

place in Oklahoma.

**3.5 Minimum Requirements for 800 MHz Radio Equipment (806 – 870 MHz) Post Rebanding**

- FCC Part 90 Type Accepted
- Equipped with P25 software
- Capable Continuous Tone-Coded Squelch System (CTCSS)
- In Compliance with FCC NPSPAC emissions 16K0F3E and 20K0F3E
- Minimum of 12 character alpha numeric display
- Minimum of 256 channels (talkgroups) for both mobile and portable radios
- Minimum of 10 watts power for all mobile radio equipment
- Minimum of 3 watts for all portable radio equipment
- In compliance with Mil Spec 810 C, 810 D, 810 E and 810 F
- Programmed with the Non-Federal 800 MHz National Interoperability Frequencies as defined in the 800 MHz tables listed below

All new 800 MHz radio equipment must be programmed with both the pre- and post-rebanding national interoperability channels as defined by NPSTC’s Channel Naming Report dated June, 13<sup>th</sup> 2007. Any use as a base station, repeater or control station will require an FCC radio license and approval from Oklahoma NPSPAC Region 34. However, the 800 MHz national interoperability channels are covered by a “blanket authorization” from the FCC for mobile operation. Mobile operation is an FCC reference to a radio frequency that is only to be used in a mobile or portable radio. The FCC is currently in the process of rebanding the 800 MHz radio spectrum across the United States. Oklahoma’s rebanding will begin in 2010 and should be completed within thirty-six (36) months. All pre-rebanding information specific to the 800 MHz spectrum will be removed from this document upon completion of the 800 MHz rebanding initiative.

**3.5.1 Repeated 800 MHz Interoperability Channels (Rebanded)**

<b>Repeated 800 MHz Interoperability Channels for Subscriber Equipment (Rebanded) ±</b>						
<b>Desc</b>	<b>NPSTC ID</b>	<b>CTCSS*</b>	<b>TX Freq</b>	<b>Authorized Use</b>	<b>RX Freq</b>	<b>Authorized Use</b>
Calling	8CALL90	156.7 Hz	806.0125	Mobile Output	851.0125	Mobile Input
Tactical	8TAC91	156.7 Hz	806.5125	Mobile Output	851.5125	Mobile Input
Tactical	8TAC92	156.7 Hz	807.0125	Mobile Output	852.0125	Mobile Input
Tactical	8TAC93	156.7 Hz	807.5125	Mobile Output	852.5125	Mobile Input
Tactical	8TAC94	156.7 Hz	808.0125	Mobile Output	853.0125	Mobile Input

\*Default operation should be carrier squelch receive, CTCSS 156.7(5A) transmit. If the user can enable/disable CTCSS without reprogramming the radio, the indicated CTCSS tone should also be programmed for receive, and the user instructed how and when to enable/disable.

± This information included in this table will become applicable upon completion of the 800 MHz rebanding initiative currently taking place in Oklahoma.

### 3.5.2 Simplex 800 MHz Interoperability Channels (Rebanded)

Simplex 800 MHz Interoperability Channels for Subscriber Equipment (Rebanded) ±						
Desc	NPSTC ID	CTCSS*	TX Freq	Authorized Use	RX Freq	Authorized Use
Calling	8CALL90D	156.7 Hz	851.0125	Mobile Direct Output	851.0125	Mobile Direct Input
Tactical	8TAC91D	156.7 Hz	851.5125	Mobile Direct Output	851.5125	Mobile Direct Input
Tactical	8TAC92D	156.7 Hz	852.0125	Mobile Direct Output	852.0125	Mobile Direct Input
Tactical	8TAC93D	156.7 Hz	852.5125	Mobile Direct Output	852.5125	Mobile Direct Input
Tactical	8TAC94D	156.7 Hz	853.0125	Mobile Direct Output	853.0125	Mobile Direct Input

\*Default operation should be carrier squelch receive, CTCSS 156.7(5A) transmit. If the user can enable/disable CTCSS without reprogramming the radio, the indicated CTCSS tone should also be programmed for receive, and the user instructed how and when to enable/disable.

D – Denotes low side of the frequency pair in direct (simplex) mode

± This information included in this table will become applicable upon completion of the 800 MHz rebanding initiative currently taking place in Oklahoma.

### 3.6 Communication Equipment Accessories

To date, the minimum requirements for radio equipment accessories have not been defined by the IOCSS. This section will be updated after further assessment by the IOCSS.